

Last information update: June 2025

**Product configuration: 059B**

059B: Robin spotlight Ø37 for installation on a 48V low voltage track - DALI Powerline

**Product code**

059B: Robin spotlight Ø37 for installation on a 48V low voltage track - DALI Powerline

**Technical description**

Miniaturised adjustable spotlight with adapter for installation on 48V low voltage track. Made of die-cast aluminium with passive dissipation system. The adapter made of a thermoplastic material includes the DC/DC driver circuit with a DALI Powerline dimmable function. Integrated «power line» technology allows each spotlight on the track to be adjusted separately. The swivel joints allow the spotlight to be rotated by 360° and tilted by 160° with the option of installing the spotlight on a 48V track in both an "up" and "down" position. The set back position of the optic unit guarantees a high level of visual comfort. A high definition thermoplastic lens with the option of using additional accessories to create other light effects. A rapid tool-free system for connecting the adapter electrically and mechanically to the track. The 48V track coupling device is fitted with a mechanical anti-fall safety double block.

**Installation**

An adapter is used to fix the device mechanically and tool-free to the 48V track.

**Colour**

White (01) | Black (04)


**Weight (Kg)**

0.25

**Wiring**

Driver DC/DC with a DALI Powerline dimmable function - direct connection on 48V track. Track power supply unit to be ordered separately.

Complies with EN60598-1 and pertinent regulations

**Technical data**

|  |       |                                       |   |
|--|-------|---------------------------------------|---|
| Im system:   | 564.0 | MacAdam Step:                         | 2                                       |
| W system:  | 11.3  | Life Time LED 1:                      | > 50,000h - L90 - B10 (Ta 25C)          |
| Im source:   | 940   | Voltage [Vin]:                        | 48                                      |
| W source:  | 9.6   | Lamp code:                            | LED                                     |
| Luminous efficiency (lm/W, real value):            | 49.91 | Number of lamps for optical assembly: | 1                                       |
| Im in emergency mode:                              | -     | ZVEI Code:                            | LED                                     |
| Total light flux at or above an angle of 90° [Lm]: | 0.0   | Number of optical assemblies:         | 1                                       |
| Light Output Ratio (L.O.R.) [%]:                   | 60    | Power factor:                         | See installation instructions           |
| Beam angle [°]:                                    | 45°   | Minimum dimming %:                    | 5                                       |
| CRI:   | 90    | Overvoltage protection:               | 0kV Common mode & 0kV Differential mode |
| Colour temperature [K]:                            | 3500  | Control:                              | DALI                                    |