


Last information update: May 2025

Product configuration: 175A.01

175A.01: SIPARIO Ø73 spotlight - CASAMBI - Spot - OBLens - - 12.9W 903lm - 4000K - CRI 90 - White

**Product code**

175A.01: SIPARIO Ø73 spotlight - CASAMBI - Spot - OBLens - - 12.9W 903lm - 4000K - CRI 90 - White

Technical description

Ø73 adjustable spotlight with adapter for installation on a base or electrified track. LED lamp with C.O.B. (Chip on board) technology, -CRI90- high colour rendering and 4000K tone.

Die-cast aluminium body with thermoplastic rear cap and front ring (Mass-Balance). The product can be rotated by 360° around the vertical axis with a mechanical lock and tilted by 90° relative to the horizontal plane. Passive heat dissipation.

OptiBeam Lens optical system with Spot optic.

Body complete with dimmable power supply unit and Casambi protocol positioned inside the product track adapter. The components used allow the products to be controlled with the Casambi system app and components, enabling on-off, dimming and scene recall functions and allowing multiple luminaires to operate in a Casambi mesh network. 2.4 GHz bluetooth frequency. The app is available on the Apple Store and Google Play Store. Integrated Beacon that can be activated via an app (iBeacon) that enables smart functions for third party applications and the Jiminy Push Notification app.

Spotlight with Push&Go system designed to facilitate and safely accelerate the connection between product and optic accessory.

Mechanically disconnecting the accessory allows it to be disengaged but not dropped. Three internal accessories and one external one can be used simultaneously. All internal accessories rotate 360° about the spotlight longitudinal axis.

Installation

Base or mains voltage track.

Colour

White (01)

Weight (Kg)

0.65

Mounting

three circuit track

Notes

Max distance between product and product 8 m.


The maximum distance is affected by physical obstacles, like walls, metal panels and the layout of the system.

Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	903	MacAdam Step:	2
W system:	12.9	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Im source:	1050	Lamp code:	LED
W source:	10	Number of lamps for optical assembly:	1
Luminous efficiency (Im/W, real value):	70	ZVEI Code:	LED
Im in emergency mode:	-	Number of optical assemblies:	1
Total light flux at or above an angle of 90° [Lm]:	0	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	86	Inrush current:	20 A / 25 µs
Beam angle [°]:	9° / 10°	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 81 luminaires B16A: 130 luminaires C10A: 135 luminaires C16A: 221 luminaires
CRI (minimum):	90	Overvoltage protection:	2kV Common mode & 1kV Differential mode
Colour temperature [K]:	4000	Control:	Casambi

Polar

Imax=22833 cd		Lux			
		h	d	Em	Emax
		2	0.3	4403	5708
		4	0.6	1101	1427
		6	0.9	489	634
		8	1.2	275	357
$\alpha=9^{\circ} / 10^{\circ}$					

