

## Palco Low Voltage


Design Artec  
Studio

iGuzzini

Last information update: June 2025

### Product configuration: 951A

951A: Palco LV spotlight 2 x Ø 19 - spot beam - DALI Powerline



### Product code

951A: Palco LV spotlight 2 x Ø 19 - spot beam - DALI Powerline

### Technical description

Lighting assembly consisting of two miniaturised adjustable spotlights with adapter for installation on 48V low voltage track. Spotlight bodies made of die-cast zamak with a passive dissipation system. The adapter made of a thermoplastic material includes the DC/DC driver circuit with a DALI dimmable function. Integrated «Powerline» technology allows each spotlight installed on the track to be adjusted separately; in the paired spotlight model adjustment is synchronous for both lighting bodies. The spotlight swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic units guarantees a high level of visual comfort with thermoplastic high definition lenses. A rapid tool-free system for connecting the adapter electrically and mechanically to the track.

### Installation

An adapter is used to fix the device mechanically and tool-free to the 48V track.

### Colour

White (01) | Black (04)

### Weight (Kg)

0.09

### Mounting

Low voltage track

### Wiring

Integrated DC/DC LED driver in adapter - direct connection on 48V track. Track power supply unit to be ordered separately.

Complies with EN60598-1 and pertinent regulations



IP20



### Technical data

lm system:	244.0	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25C)
W system:	5.4	Voltage [Vin]:	48
lm source:	200	Lamp code:	LED
W source:	2	Number of lamps for optical assembly:	1
Luminous efficiency (lm/W, real value):	45.19	ZVEI Code:	LED
lm in emergency mode:	-	Number of optical assemblies:	2
Total light flux at or above an angle of 90° [Lm]:	0.0	LED current [mA]:	0.7
Light Output Ratio (L.O.R.) [%]:	61	Power factor:	See installation instructions
Beam angle [°]:	14°	Minimum dimming %:	5
CRI:	90	Overvoltage protection:	0kV Common mode & 0kV Differential mode
Colour temperature [K]:	3500	Control:	DALI
MacAdam Step:	2		