



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2018011001047704

Valid from: Jun.15,2023

Valid until: Jun.14,2028

NAME AND REGISTERED ADDRESS OF THE APPLICANT iGuzzini illuminazione S.p.A.
Via Mariano Guzzini, 37 62019 Recanati, Italy

NAME AND REGISTERED ADDRESS OF THE MANUFACTURER iGuzzini illuminazione S.p.A.
Via Mariano Guzzini, 37 62019 Recanati, Italy

NAME AND LOCATION OF THE FACTORY iGuzzini illuminazione S.p.A.
Via Mariano Guzzini, 37 62019 Recanati, Italy

PRODUCT MODEL(S) Ground Recessed Luminaires (Ground Recessed Luminaire, A.C. Supplied Electronic Controlgear For LED Modules, ClassII, IP65, IP67, Suitable For Direct Mounting On Normally Flammable Material, Not Covered By Insulating Material)
See Appendix. 220/240V ~ 50/60Hz

STANDARDS AND TECHNICAL REQUIREMENTS GB/T 17743-2021;GB 7000.1-2015;GB 7000.213-2008

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C10-01:2014)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original issued: Feb.08,2018

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2018011001047704

page 1 of 1

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

不可调光:

E111 9W (1×6.6W/LED) , E112 10W (1×8.3W/LED) , E113 10W (1×8.3W/LED) , E114 10W (1×8.3W/LED) ,
E115 9W (1×6.6W/LED) , E116 10W (1×8.3W/LED) , E117 10W (1×8.3W/LED) , E118 10W (1×8.3W/LED) ,
E119 12.5W (1×9.6W/LED) , E120 12.5W (1×9.6W/LED) , E121 9W (1×6.6W/LED) , E122 9W (1×6.6W/LED) ,
E123 7W (1×5W/LED) , E124 7W (1×5W/LED) ,

控制端口调光 (DALI 调光):

E125 9W (1×6.6W/LED) , E126 9W (1×6.6W/LED) , E127 11.7W (1×7.9W/LED) , E128 15W (1×12W/LED) ,
E129 14.5W (1×12W/LED) , E130 14.5W (1×12W/LED) , E131 14.5W (1×12W/LED) , E132 11.7W (1×7.9W/LED) , E133 15W (1×
12W/LED) , E134 14.5W (1×12W/LED) , E135 14.5W (1×12W/LED) , E136 14.5W (1×12W/LED) , E139 15W (1×12W/LED) , E140
15W (1×12W/LED) , E141 11W (1×7.9W/LED) , E142 14W (1×10W/LED) ,
E143 14W (1×10W/LED) , E144 14W (1×10W/LED) , E145 11W (1×7.9W/LED) , E146 14W (1×10W/LED) ,
E147 14W (1×10W/LED) , E148 14W (1×10W/LED) , E149 11.5W (1×7.9W/LED) , E150 14.3W (1×12W/LED) ,
E151 21.4W (1×18W/LED) , E152 21.4W (1×18W/LED) , E153 21.4W (1×18W/LED) , E154 11.5W (1×7.9W/LED) ,
E155 14.3W (1×12W/LED) , E156 21.4W (1×18W/LED) , E157 21.4W (1×18W/LED) , E158 21.4W (1×18W/LED) , E161 14.3W (1
×12W/LED) , E162 14.3W (1×12W/LED) , E169 12W (1×7.9W/LED) , E170 18W (1×14W/LED) ,
E171 18W (1×14W/LED) , E172 18W (1×14W/LED) , E173 12W (1×7.9W/LED) , E174 18W (1×14W/LED) ,
E175 18W (1×14W/LED) , E176 18W (1×14W/LED).

220/240V ~ 50/60Hz.

本灯具额定载荷 50kN , 额定最大表面温度 T : 40°C , 安装后突出地面高度 0mm ; 预期的使用区域 : 在限制触及的区域 , 例如 : 仅步行和脚踏车区域。



CHINA QUALITY CERTIFICATION CENTRE



中国国家强制性产品认证证书

证书编号: 2018011001047704

发证日期: 2023 年 06 月 15 日

有效期至: 2028 年 06 月 14 日

认证委托人名称 iGuzzini illuminazione S.p.A.

及注册地址 Via Mariano Guzzini, 37 62019 Recanati, 意大利

产品生产者名称 iGuzzini illuminazione S.p.A.

及注册地址 Via Mariano Guzzini, 37 62019 Recanati, 意大利

生产企业名称 iGuzzini illuminazione S.p.A.

及生产地址 Via Mariano Guzzini, 37 62019 Recanati, 意大利

产品名称和系列、规格、型号 地面嵌入式灯具 (嵌地面式, LED 模块用交流电子控制装置, II 类, IP65/IP67, 适宜直接安装在普通可燃材料表面, 不能被隔热材料覆盖)
见附件. 220/240V ~ 50/60Hz

产品标准和技术要求 GB/T 17743-2021; GB 7000.1-2015; GB 7000.213-2008

上述产品符合 CNCA-C10-01:2014 认证规则的要求, 特发此证。

证书有效期内本证书的有效性依据发证机构的定期监督获得保持。

本证书为变更证书, 证书首次颁发日期: 2018 年 02 月 08 日

经中国合格评定国家认可委员会认可 CNAS C001-P

可通过扫描下方二维码或登录国家认监委网站 (www.cnca.gov.cn) 查验证书信息



签发:

谢肇煦



中国质量认证中心



中国国家强制性产品认证证书

证书编号: 2018011001047704

第 1 页 / 共 1 页

本证书及附件应同时使用, 信息查验说明见证书页

纸号:

不可调光:

E111 9W (1×6.6W/LED), E112 10W (1×8.3W/LED), E113 10W (1×8.3W/LED), E114 10W (1×8.3W/LED),
E115 9W (1×6.6W/LED), E116 10W (1×8.3W/LED), E117 10W (1×8.3W/LED), E118 10W (1×8.3W/LED),
E119 12.5W (1×9.6W/LED), E120 12.5W (1×9.6W/LED), E121 9W (1×6.6W/LED), E122 9W (1×6.6W/LED),
E123 7W (1×5W/LED), E124 7W (1×5W/LED),

控制端口调光 (DALI 调光):

E125 9W (1×6.6W/LED), E126 9W (1×6.6W/LED), E127 11.7W (1×7.9W/LED), E128 15W (1×12W/LED),
E129 14.5W (1×12W/LED), E130 14.5W (1×12W/LED), E131 14.5W (1×12W/LED), E132 11.7W (1×7.9W/LED),
E133 15W (1×12W/LED), E134 14.5W (1×12W/LED), E135 14.5W (1×12W/LED),
E136 14.5W (1×12W/LED), E139 15W (1×12W/LED), E140 15W (1×12W/LED), E141 11W (1×7.9W/LED),
E142 14W (1×10W/LED),
E143 14W (1×10W/LED), E144 14W (1×10W/LED), E145 11W (1×7.9W/LED), E146 14W (1×10W/LED),
E147 14W (1×10W/LED), E148 14W (1×10W/LED), E149 11.5W (1×7.9W/LED), E150 14.3W (1×12W/LED),
E151 21.4W (1×18W/LED), E152 21.4W (1×18W/LED), E153 21.4W (1×18W/LED), E154 11.5W (1×7.9W/LED),
E155 14.3W (1×12W/LED), E156 21.4W (1×18W/LED), E157 21.4W (1×18W/LED), E158 21.4W (1×18W/LED),
E161 14.3W (1×12W/LED), E162 14.3W (1×12W/LED), E169 12W (1×7.9W/LED),
E170 18W (1×14W/LED),
E171 18W (1×14W/LED), E172 18W (1×14W/LED), E173 12W (1×7.9W/LED), E174 18W (1×14W/LED),
E175 18W (1×14W/LED), E176 18W (1×14W/LED).

220/240V ~ 50/60Hz.

本灯具额定载荷 50kN, 额定最大表面温度 T : 40℃, 安装后突出地面高度 0mm; 预期的使用区域: 在限制触及的区域, 例如: 仅步行和脚踏车区域。



中国质量认证中心