

**Product configuration: EL67**

EL67: 47 surface Remote – Warm White – 48 Vdc DALI – L=908mm – Wide Flood optic



EL67: 47 surface Remote – Warm White – 48 Vdc DALI – L=908mm – Wide Flood optic

Direct light luminaire, designed to use monochrome LED lamps, DALI 48Vdc dimmable with searching and addressing function. Ceiling-, wall- or surface-mounted. Consists of a body and supports for installation, to be ordered separately. The body is made of extruded aluminium and includes die-cast aluminium end caps with 50/60 Shore A silicone seals. It is subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The following painting stage consists of a primer and a liquid acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. The top of the optical assembly is closed by a 3 mm thick transparent glass screen, fixed with silicone. Complete with multi-LED plate in Warm White and a 48V dc DALI electronic driver (ballast to be ordered separately). Supplied with a double PG11 and outlet cables for pass-through wiring with IP68 male/female joiners. Fitted with a PMMA diffusing filter and optics with plastic (methacrylate) lens for Wide Flood lighting. All external screws used are made of A2 stainless steel. The luminaire technical characteristics conform to EN 60598-1 standards and particular requirements.

Accessories are available for installation, like adjustable AISI304 stainless steel wall-mounted arms.

White (01) | Black (04) | Grey (15) | Rust Brown (F5)

## 2.6

wall arm|wall surface|ceiling surface

Complete with DALI 44+52Vdc control card. The product is supplied with a nickel-plated brass PG11 double cable gland with 05RN-F 2x1,5mm<sup>2</sup>×3x0,35mm<sup>2</sup> rubber outlet cables for pass-through wiring with joiners (illegible part). Available for electrical connection and DALI control: IP68 4-pin female connector, IP68 4-pin male connector + closing cap (BZI6), and IP68 4-pin male + female connectors.

Product complete with LED lamp.

Complies with EN60598-1 and pertinent regulations



Im system:	2340	MacAdam Step:	3
W system:	35.6	Life Time LED 1:	100,000h - L80 - B10 (Ta 25°C)
Im source:	3900	Life Time LED 2:	100,000h - L80 - B10 (Ta 40°C)
W source:	31	Voltage [Vin]:	48
Luminous efficiency (lm/W, real value):	65.7	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	60	Number of optical assemblies:	1
Beam angle [°]:	42° / 44°	Intervallo temperatura ambiente:	from -30°C to 50°C.
CRI (minimum):	80	Control:	DALI-2
Colour temperature [K]:	2700		

Lux	h	d1	d2	Em	Emax
4	3.1	3.2	174	232	
8	6.1	6.5	44	58	
12	9.2	9.7	19	26	
16	12.3	12.9	11	15	

# Isolux

