


Last information update: May 2025

Product configuration: JYX3

JYX3: Applique with DMX driver included - 360° Blade effect optic

**Product code**

JYX3: Applique with DMX driver included - 360° Blade effect optic

Technical description

Wall and ceiling-mounted luminaire, designed for use with LED lamps and a patented, 360° blade effect optic. The product consists of a support base and a screen with DMX driver included. The base is made of phosphocromatization treated, die-cast aluminium, with a double base coat and passivation at 120°C. It is coated with liquid acrylic paint, cured at 150 °C to guarantee a high level of weather and UV ray resistance. The optic is made of methacrylate. All the screws used are made of A2 stainless steel.

Installation

Wall and ceiling mounted by means of a stainless steel wall fixture plate.

Colour

White (01) | Black (04) | Grey (15) | Rust Brown (F5)

Weight (Kg)

1.35

Mounting

wall surface|ceiling surface

Notes


wall/ceiling-mounted

Complies with EN60598-1 and pertinent regulations



IK07

IP66

**Technical data**

Im system:	35
W system:	7.6
Im source:	160
W source:	6
Luminous efficiency (lm/W, real value):	4.6
Im in emergency mode:	-
Total light flux at or above an angle of 90° [Lm]:	11
Light Output Ratio (L.O.R.) [%]:	22
Colour temperature [K]:	RGB
Life Time LED 1:	100,000h - L80 - B10 (Ta 25°C)

Voltage [Vin]:	48
Lamp code:	LED
Number of lamps for optical assembly:	1
ZVEI Code:	LED
Number of optical assemblies:	1
Intervallo temperatura ambiente:	from -30°C to 35°C.
Lifetime of product at ambient operating temperature:	≥ 50.000h Ta=25°C
LED current [mA]:	450
Control:	DMX-RDM

Polar