


Last information update: May 2025

**Product configuration: JYX3**

JYX3: Applique with DMX driver included - 360° Blade effect optic

**Product code**

JYX3: Applique with DMX driver included - 360° Blade effect optic

**Technical description**

Wall and ceiling-mounted luminaire, designed for use with LED lamps and a patented, 360° blade effect optic. The product consists of a support base and a screen with DMX driver included. The base is made of phosphocromatization treated, die-cast aluminium, with a double base coat and passivation at 120°C. It is coated with liquid acrylic paint, cured at 150 °C to guarantee a high level of weather and UV ray resistance. The optic is made of methacrylate. All the screws used are made of A2 stainless steel.

**Installation**

Wall and ceiling mounted by means of a stainless steel wall fixture plate.

**Colour**

White (01) | Black (04) | Grey (15) | Rust Brown (F5)

**Weight (Kg)**

1.35

**Mounting**

wall surface|ceiling surface

**Notes**


wall/ceiling-mounted

Complies with EN60598-1 and pertinent regulations



IK07

IP66

**Technical data**

Im system:	59	Voltage [Vin]:	48
W system:	7.7	Lamp code:	LED
Im source:	360	Number of lamps for optical assembly:	1
W source:	5	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	7.7	Number of optical assemblies:	1
Im in emergency mode:	-	Intervallo temperatura ambiente:	from -30°C to 35°C.
Total light flux at or above an angle of 90° [Lm]:	19	Lifetime of product at ambient operating temperature:	≥ 50.000h Ta=25°C
Light Output Ratio (L.O.R.) [%]:	17	LED current [mA]:	150
Colour temperature [K]:	RGB	Control:	DMX-RDM
Life Time LED 1:	100,000h - L80 - B10 (Ta 25°C)		

**Polar**