


Design iGuzzini iGuzzini



lm system:	2115	CRI (typical):	97
W system:	35	Colour temperature [K]:	2700
lm source:	2550	MacAdam Step:	3
W source:	31	Life Time LED 1:	50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	60.4	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	83	Number of optical assemblies:	1
Beam angle [°]:	48°	Control:	DALI-2
CRI (minimum):	95		

	Imax=3745 cd 90° 180° 90° 4000 0° α=48°	CIE nL 0.83 100-100-100-100-83 UGR <10-10 DIN A.61 UTE 0.83A+0.00T F*1=999 F*1+F*2=1000 F*1+F*2+F*3=1000 CIBSE LG3 L<1500 cd/m² at 65° UGR<10 L<1500 cd/mq @65°	Lux <table border="1"> <thead> <tr> <th>h</th> <th>d</th> <th>Em</th> <th>Emax</th> </tr> </thead> <tbody> <tr> <td>2</td> <td>1.8</td> <td>784</td> <td>934</td> </tr> <tr> <td>4</td> <td>3.6</td> <td>196</td> <td>234</td> </tr> <tr> <td>6</td> <td>5.3</td> <td>87</td> <td>104</td> </tr> <tr> <td>8</td> <td>7.1</td> <td>49</td> <td>58</td> </tr> </tbody> </table>	h	d	Em	Emax	2	1.8	784	934	4	3.6	196	234	6	5.3	87	104	8	7.1	49	58
	h	d	Em	Emax																			
	2	1.8	784	934																			
	4	3.6	196	234																			
	6	5.3	87	104																			
8	7.1	49	58																				

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	75	71	68	66	70	68	68	65	78
1.0	78	75	72	70	74	72	71	69	83
1.5	82	79	77	76	79	77	76	74	89
2.0	85	83	81	80	82	80	79	77	93
2.5	86	85	84	83	84	83	82	79	96
3.0	87	86	85	85	85	84	83	81	98
4.0	88	87	87	86	86	86	84	82	99
5.0	89	88	88	88	87	86	85	83	100

UGR diagram

Corrected UGR values (at 2550 lm bare lamp luminous flux)											
Riflect.:		viewed crosswise					viewed endwise				
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim		viewed crosswise					viewed endwise				
x	y										
2H	2H	1.4	1.9	1.7	2.1	2.4	1.4	1.9	1.7	2.1	2.4
	3H	1.3	1.7	1.6	2.0	2.3	1.3	1.7	1.6	2.0	2.3
	4H	1.2	1.6	1.5	1.9	2.2	1.2	1.6	1.5	1.9	2.2
	6H	1.1	1.5	1.5	1.8	2.1	1.1	1.5	1.5	1.8	2.1
	8H	1.1	1.5	1.5	1.8	2.1	1.1	1.5	1.5	1.8	2.1
	12H	1.1	1.4	1.4	1.8	2.1	1.1	1.4	1.4	1.7	2.1
4H	2H	1.2	1.6	1.5	1.9	2.2	1.2	1.6	1.5	1.9	2.2
	3H	1.1	1.4	1.4	1.7	2.1	1.1	1.4	1.4	1.8	2.1
	4H	1.0	1.3	1.4	1.6	2.0	1.0	1.3	1.4	1.6	2.0
	6H	0.9	1.2	1.3	1.6	2.0	0.9	1.2	1.3	1.6	2.0
	8H	0.8	1.1	1.3	1.5	1.9	0.8	1.1	1.3	1.5	1.9
	12H	0.8	1.0	1.2	1.4	1.9	0.8	1.0	1.2	1.4	1.9
8H	4H	0.8	1.1	1.3	1.5	1.9	0.8	1.1	1.3	1.5	1.9
	6H	0.8	1.0	1.2	1.4	1.9	0.8	1.0	1.2	1.4	1.9
	8H	0.7	0.9	1.2	1.3	1.8	0.7	0.9	1.2	1.3	1.8
	12H	0.6	0.8	1.1	1.3	1.8	0.6	0.8	1.1	1.3	1.8
12H	4H	0.8	1.0	1.2	1.4	1.9	0.8	1.0	1.2	1.4	1.9
	6H	0.7	0.9	1.2	1.3	1.8	0.7	0.9	1.2	1.3	1.8
	8H	0.6	0.8	1.1	1.3	1.8	0.6	0.8	1.1	1.3	1.8
Variations with the observer position at spacing:											
S =		1.0H	0.9 / -18.0				0.9 / -18.0				
		1.5H	9.7 / -18.3				9.7 / -18.3				
		2.0H	11.7 / -18.4				11.7 / -18.4				