

## Laser Blade


Design iGuzzini

iGuzzini

Last information update: April 2025

### Product configuration: MQ40

MQ40: Adjustable 2 x 15 - cell Recessed frame - LED - Warm white - DALI dimmable power supply - Flood Beam



### Product code

MQ40: Adjustable 2 x 15 - cell Recessed frame - LED - Warm white - DALI dimmable power supply - Flood Beam

### Technical description

Recessed rectangular luminaire with LEDs. Shaped steel sheet structural compartment with outer rim. The two linear elements with 15 lighting cells, in die-cast aluminium and independently adjustable, can be used to direct the emission with a tilting adjustability of +/- 30°. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen; the structure of the optical system prevents a pinpoint effect, allowing precise, circular light distribution and emission with controlled glare. Supplied with DALI dimmable control gear connected to the luminaire. Warm white high chromatic yield LED.

### Installation

recessed with mechanical blocking system for false ceilings from 1 to 25 mm; can be installed on ceilings and walls (vertical + horizontal) - preparation slot 135 x 428

### Colour

Black / Black (43) | Black / White (47) | Grey / Black (74)\*

### Weight (Kg)

3.36

\* Colours on request

### Mounting

wall recessed|ceiling recessed

### Wiring

On power box: screw and quick release connections. The product is fitted with a separate control gear for each lighting body; possibility of separate switching

### Notes

dimming function with pushbutton (TOUCH DIM/PUSH): for this option consult the instructions included in the package

Complies with EN60598-1 and pertinent regulations



### Technical data

lm system:	4312.98	CRI:	95
W system:	70.0	Colour temperature [K]:	3000
lm source:	2700	MacAdam Step:	3
W source:	30	Life Time LED 1:	50,000h - L90 - B10 (Ta 25C)
Luminous efficiency (lm/W, real value):	61.61	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	80	Number of optical assemblies:	2
Beam angle [°]:	31°	Control:	DALI-2