

Last information update: May 2025

### Product configuration: MV99.Y

MV99.Y: Fixed circular recessed luminaire - Ø125 mm - warm white - wide flood optic - UGR<19



### Product code

MV99.Y: Fixed circular recessed luminaire - Ø125 mm - warm white - wide flood optic - UGR<19

### Technical description

Fixed round luminaire designed to use a LED lamp with C.O.B. technology. Version with rim for surface-mounting. Reflector vacuum-metallised with aluminium vapours with an anti-scratch protective layer. Die-cast aluminium body and passive dissipation system. Product complete with LED lamp in warm white colour tone (3000K). General light emission, with controlled luminance UGR<19 1500 cd/m<sup>2</sup> α>65° wide flood optic.

### Installation

Recessed using torsion springs which allow easy installation in false ceilings with thickness ranging from 1 mm to 20 mm.

### Colour

White / Aluminium (39)


### Mounting

ceiling recessed

### Wiring

product complete with an electronic ballast

Complies with EN60598-1 and pertinent regulations



IP20

IP54

On the visible part of  
the product once installed



### Technical data

lm system:	2145.18	CRI:	80
W system:	19.8	Colour temperature [K]:	3000
lm source:	2650	MacAdam Step:	2
W source:	17	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
Luminous efficiency (lm/W, real value):	108.34	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	81	Number of optical assemblies:	1
Beam angle [°]:	64°		