


Product configuration: N079

N079: adjustable luminaire - Ø 96 mm - warm white - medium optic - frame



Product code

N079: adjustable luminaire - Ø 96 mm - warm white - medium optic - frame

Technical description

Round adjustable luminaire designed to use an LED lamp with C.O.B. technology in a warm white colour tone 3000K (CRI 90). Version with rim for surface-mounting. Painted, die-cast aluminium body. Lower reflector vacuum-metallised with aluminium vapours with an anti-scratch protective layer. Anodised aluminium upper reflector. Black, zinc-plated sheet steel bracket. The luminaire can be rotated 30° relative to the horizontal plane and 358° about the vertical axis. The luminaire is fitted with mechanical locks for light beam aiming. Painted extruded aluminium dissipater.

Installation

Recessed using torsion springs which allow easy installation in false ceilings with thickness ranging from 1 mm to 25 mm.

Colour
White / Aluminium (39)

Weight (Kg)
0.49

Mounting

ceiling recessed

Wiring

Product complete with DALI components

Notes

Tpa rated


Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	780	CRI (minimum):	90
W system:	16.5	Colour temperature [K]:	3000
Im source:	1700	MacAdam Step:	2
W source:	14	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	47.2	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	46	Number of optical assemblies:	1
Beam angle [°]:	25°	Control:	DALI-2


Polar



Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	41	39	38	37	39	37	37	36	78
1.0	43	41	40	39	41	40	39	38	83
1.5	45	44	43	42	43	42	42	41	88
2.0	47	46	45	44	45	44	44	43	93
2.5	48	47	46	46	46	46	45	44	96
3.0	48	48	47	47	47	46	46	45	98
4.0	49	48	48	48	48	47	47	46	99
5.0	49	49	48	48	48	48	47	46	100

Luminance curve limit



UGR diagram

Corrected UGR values (at 1700 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		viewed crosswise					viewed endwise				
		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
2H	2H	0.8	2.9	1.2	3.3	3.6	0.4	2.6	0.8	2.9	3.3
	3H	0.6	2.3	1.0	2.7	3.0	0.3	2.0	0.7	2.3	2.7
	4H	0.6	2.0	1.0	2.3	2.7	0.3	1.7	0.6	2.0	2.3
	6H	0.6	1.6	0.9	2.0	2.3	0.2	1.3	0.6	1.6	2.0
	8H	0.5	1.6	0.9	1.9	2.3	0.2	1.2	0.6	1.6	1.9
	12H	0.5	1.5	0.9	1.8	2.2	0.1	1.1	0.5	1.5	1.9
4H	2H	0.6	2.0	1.0	2.3	2.7	0.2	1.6	0.6	2.0	2.3
	3H	0.5	1.5	0.9	1.8	2.2	0.1	1.2	0.5	1.5	1.9
	4H	0.4	1.3	0.8	1.7	2.1	0.0	1.0	0.5	1.4	1.8
	6H	-0.0	1.7	0.5	2.1	2.6	-0.3	1.4	0.1	1.8	2.3
	8H	-0.1	1.8	0.4	2.2	2.7	-0.5	1.4	0.0	1.9	2.4
	12H	-0.2	1.8	0.3	2.2	2.8	-0.6	1.4	-0.1	1.9	2.4
8H	4H	-0.2	1.8	0.3	2.2	2.7	-0.5	1.4	0.0	1.9	2.4
	6H	-0.3	1.6	0.2	2.1	2.6	-0.6	1.2	-0.1	1.7	2.3
	8H	-0.3	1.4	0.2	1.9	2.4	-0.6	1.0	-0.1	1.5	2.1
	12H	-0.1	1.0	0.4	1.5	2.0	-0.5	0.6	0.1	1.1	1.7
12H	4H	-0.3	1.7	0.2	2.2	2.7	-0.6	1.4	-0.1	1.9	2.4
	6H	-0.3	1.4	0.2	1.9	2.4	-0.6	1.0	-0.1	1.5	2.1
	8H	-0.1	1.0	0.4	1.5	2.0	-0.4	0.6	0.1	1.1	1.7
Variations with the observer position at spacing:											
S =	1.0H	3.9 / -8.6					4.4 / -9.8				
	1.5H	6.7 / -13.5					7.2 / -11.8				
	2.0H	8.6 / -13.5					9.2 / -14.1				