

Laser Blade


Design iGuzzini

iGuzzini

Last information update: March 2025

Product configuration: P129.41

P129.41: 5 - cell Recessed luminaire - LED - Warm white - Incorporated DALI dimmable power supply - Spot optic - 13W 902lm - 3000K - CRI 90 - White/Gold

**Product code**

P129.41: 5 - cell Recessed luminaire - LED - Warm white - Incorporated DALI dimmable power supply - Spot optic - 13W 902lm - 3000K - CRI 90 - White/Gold

Technical description

rectangular miniaturised recessed luminaire with 5 optical elements with LED lamps - fixed optics - spot beam angle. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen; the structure of the optical system prevents a pinpoint effect, allowing precise, circular light distribution and emission with controlled glare . Supplied with DALI dimmable electronic control gear connected to the luminaire.

Installation

recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 37 x 141

Colour

White/Gold (41)*

Weight (Kq)

0.3

* Colours on request

Mounting

mounting
wall recessed|ceiling recessed

Wiring

on control gear box: screw connections with terminal block included


Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	902	CRI (typical):	92
W system:	13	Colour temperature [K]:	3000
Im source:	1100	MacAdam Step:	3
W source:	9.9	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	69.4	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	82	Number of optical assemblies:	1
Beam angle [°]:	14°	Control:	DALI-2
CRI (minimum):	90		

Polar



Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	74	70	68	66	70	67	67	64	78
1.0	77	74	72	70	73	71	71	68	83
1.5	81	79	77	75	78	76	75	73	89
2.0	84	82	80	79	81	79	78	76	93
2.5	85	84	83	82	83	82	81	79	96
3.0	86	85	84	84	84	83	82	80	98
4.0	87	86	86	85	85	85	83	82	99
5.0	88	87	87	87	86	85	84	82	100
