


Last information update: April 2025

Product configuration: P525

P525: Fixed circular recessed luminaire - Ø125 mm - natural white - wide flood optic - UGR<10 - DALI

**Product code**

P525: Fixed circular recessed luminaire - Ø125 mm - natural white - wide flood optic - UGR<10 - DALI

Technical description

Fixed round luminaire designed to use a LED lamp with C.O.B. technology. Version with rim for surface-mounting. Optic with super comfort reflector vacuum-metallised with aluminium vapours and an anti-scratch protective layer. Die-cast aluminium body and passive dissipation system. Product complete with LED lamp in neutral white colour tone (4,000K). General light emission, with controlled luminance UGR<10 1500 cd/m² α>65° wide flood optic.

Installation

Recessed using torsion springs which allow easy installation in false ceilings with thicknesses ranging from 1 mm to 20 mm.

Colour

White / Aluminium (39)

Weight (Kg)

1.15

Mounting

ceiling recessed

Wiring

product complete with DALI components

Notes

TPb rated

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	2434.25	CRI:	80
W system:	24.1	Colour temperature [K]:	4000
lm source:	3250	MacAdam Step:	2
W source:	21	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
Luminous efficiency (lm/W, real value):	101.01	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	75	Number of optical assemblies:	1
Beam angle [°]:	42°	Control:	DALI-2