

## Blade R downlight


Design iGuzzini

iGuzzini

Last information update: November 2024

### Product configuration: PB19.01

PB19: Round swivel luminaire



### Product code

PB19: Round swivel luminaire

### Technical description

Round swivel luminaire with 355° internal rotation and max 30 tipping movement, designed to use LED lamps with C.o.B. technology. Version compatible with Blade R diam 125mm (12LED) complete with device for coupling it to the luminaire and DALI control gear. The main swivel body is made of die-cast aluminium with a radiant surface that guarantees optimum heat dissipation. Metallised, thermoplastic, high definition reflector - medium optic (16°). Structure with die-cast aluminium external surface frame. The internal ring is made of thermoplastic available in a range of painted and metallised finishes. Safety glass included Product complete with LED with a 2700K colour tone and high colour rendering index CRI90.

### Installation

Downlight accessory for Blade R diam 125mm (12LED)

### Colour

White (01)

### Weight (Kg)

0.27

Complies with EN60598-1 and pertinent regulations



IP20

IP23

On the visible part of the product once installed



### Technical data

Im system:	482.8	Colour temperature [K]:	2700
W system:	8.1	MacAdam Step:	2
Im source:	680	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
W source:	6	Voltage [Vin]:	230
Luminous efficiency (Im/W, real value):	59.6	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	71	Number of optical assemblies:	1
Beam angle [°]:	14°	Control:	DALI-2
CRI:	90		