

Light Shed 60

Design iGuzzini

iGuzzini

Last information update: February 2024



Accessory code

PD08: Cover with multi-sensor lux and movement - BLE 5.2 – 220/240 V – Light Shed 60 | dB 60 **Attention! Code no longer in production**

Technical description

Circular cover complete with BLE multi-sensor compatible with the "Quick BLE" smart light system (Bluetooth WiSilica). The sensor detects motion (PIR) and lighting value. Devices can be programmed, enabled and connected via the Smart Light Control app available on Apple Store and Google Play Store. Frequency and protocol: 2.4 GHz Bluetooth Low Energy 5.2. Dynamic lighting range: 10-1000 lx. Trigger presence time setting range: 1 sec - 1440 min OTA (over the air) update via app. Integrated beacon that can be activated via an app (Eddystone, iBeacon and Alt Beacon protocols). Ambient temperature Ta max 25°C.

Installation

Installation on a non-luminous Light Shed 60 | dB 60 module (PC81 PC83 RC89 RC94). Assembly height: min 2.4 m / max 3 m. Cover diameter 9 m (@ h2.5 m installation). To position the cover correctly see the instruction sheet. Straight line distance from sensor-sensor, sensor-interface or sensor-smartphone: max 20 m (*)

Colour

White (01)

Weight (Kg)

0.44

Wiring

The sensor must be powered with a voltage of 230 Vac and does not require any other type of connection as information is exchanged via Bluetooth.

Notes

(*) Maximum radius of action: the maximum distance depends on the presence of fixed obstacles like concrete walls or metal panels.

Complies with EN60598-1 and pertinent regulations



IP20



Technical data

Control: Bluetooth WiSilica