


Last information update: November 2024



**Accessory code**

PE07: Power supply base with suspension cables - Ceiling-mounted luminaire - Ø234 UP-DOWN - UGR < 19

**Technical description**

Base unit for pendant/planned power supply of the structure - surface version. Shaped steel plate for coupling to the ceiling - polycarbonate covering rosette. The pre-arranged wires - L 2,500 mm - simultaneously act as suspension and power supply - the adjustment to the length and the wiring is done in the upper section of the light unit, complete with connection terminal board and safety cable clamps. Sliding devices, to be positioned along the length of the cables, allow the pendant to be aesthetically shaped. 2 DALI power supply drivers included.

**Installation**

steel plate for coupling onto the laying surface with screws and anchors (not included)

**Colour**

White (01) | Black (04)

**Weight (Kg)**

0.63

**Wiring**

connection to the network with rapid coupling terminal board positioned on the base unit plate - 2 power supply drivers included with integrated wiring. Adjustment of the power supply/pendant cables and further wiring to be done on the upper section of the light unit, arranged with connecting terminal board and safety cable clamps.

Complies with EN60598-1 and pertinent regulations



IP40

**Technical data**

Power factor: See installation instructions

Inrush current: 18 A / 250 µs

Maximum number of  
luminaires of this type per  
miniature circuit breaker:

B10A:	21 luminaires
B16A:	34 luminaires
C10A:	35 luminaires
C16A:	57 luminaires

Minimum dimming %:

1

Overvoltage protection:

2kV Common mode & 1kV  
Differential mode

Control:

DALI-2