

Last information update: March 2025

Product configuration: PG59.G0

PG59.G0: Module for Superrail 48V track - DALI - GL - L=1372 - - 19.1W 2669lm - 3500K - CRI 90 - White/White Transparent

**Product code**

PG59.G0: Module for Superrail 48V track - DALI - GL - L=1372 - - 19.1W 2669lm - 3500K - CRI 90 - White/White Transparent

Technical description

Linear lighting product with 3500K CRI90 monochrome LED complete with adapter for installation on a Superrail 48V track. General Light (High Output) luminaire with Opti-Diamond Space optic available in a White Cover (Transparent white) or Black Cover (Transparent black) version. The adapter made of a thermoplastic material includes the DC/DC driver circuit with a DALI dimmable function. Integrated «power line» technology allows each light module on the track to be adjusted separately. Frameless version main body made of extruded aluminium. A rapid tool-free system for connecting the adapter electrically and mechanically to the track.

Installation

Mechanical fastening with adapter on a Superrail 48V track

Colour

White/White Transparent (G0)

Weight (Kg)

0.75


Mounting

Low voltage track

Wiring

Integrated DC/DC LED driver in adapter - direct connection on 48V track. Track power supply unit to be ordered separately.

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	2669	Voltage [Vin]:	48
W system:	19.1	Lamp code:	LED
lm source:	3140	Number of lamps for optical assembly:	1
W source:	18	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	139.7	Number of optical assemblies:	1
lm in emergency mode:	-	LED current [mA]:	72
Total light flux at or above an angle of 90° [Lm]:	52	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	85	Minimum dimming %:	5
CRI (minimum):	90	Overvoltage protection:	2kV Common mode & 1kV Differential mode
Colour temperature [K]:	3500	Dimming mode:	CCR
MacAdam Step:	3	Control:	DALI
Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)		

Polar

Imax=2592 cd		C85-265		Lux	
h	d1	d2	Em	Emax	
4	4.7	4.6	125	158	
8	9.3	9.2	31	40	
12	14	13.9	14	18	
16	18.7	18.5	8	10	

$\alpha = 61^\circ$

Isolux

