

Last information update: October 2024

Product configuration: Q105

Q105: Fixed circular recessed luminaire - Ø125 mm - warm white - flood optic - UGR<19

**Product code**

Q105: Fixed circular recessed luminaire - Ø125 mm - warm white - flood optic - UGR<19

Technical description

Fixed round luminaire designed to use a LED lamp with C.O.B. technology. Version with rim for surface-mounting. Reflector vacuum-metallised with aluminium vapours with an anti-scratch protective layer. Die-cast aluminium body and passive dissipation system. Product complete with LED lamp in warm white colour tone (3000K). General light emission, with controlled luminance UGR<19 1500 cd/m² α>65° flood optic.

Installation

Recessed using torsion springs which allow easy installation in false ceilings with thickness ranging from 1 mm to 20 mm.

Colour

White / Aluminium (39)

Mounting

ceiling recessed

Wiring


product complete with TRIAC components

Complies with EN60598-1 and pertinent regulations



IP20

IP54

On the visible part of
the product once installed**Technical data**

lm system:	1845	CRI (minimum):	90
W system:	17.7	Colour temperature [K]:	3000
lm source:	2100	MacAdam Step:	2
W source:	16	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	104.2	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	88	Number of optical assemblies:	1
Beam angle [°]:	24°	Control:	TRIAC


Polar

Imax=4994 cd		CIE		Lux			
90°	180°	nL 0.88		h	d	Em	Emax
		98-100-100-100-88		2	0.9	944	1249
		UGR 17.1-17.1		4	1.7	236	312
		DIN		6	2.6	105	139
		A 61		8	3.4	59	78
		UTE					
		0.88A+0.00T					
		F*1=97.8					
		F*1+F*2=999					
		F*1+F*2+F*3=1000					
		CIBSE					
		LG3 L<1500 cd/m ² at 65°					
		UGR<19 L<1500 cd/mq @ 65°					
α=24°							

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	79	74	71	69	74	71	70	68	77
1.0	82	78	76	73	77	75	75	72	82
1.5	86	84	81	79	83	81	80	77	88
2.0	89	87	85	84	86	84	83	81	92
2.5	91	89	88	87	88	87	86	84	95
3.0	92	91	90	89	89	89	88	85	97
4.0	93	92	92	91	91	90	89	87	99
5.0	94	93	93	92	92	91	90	88	100

Luminance curve limit



UGR diagram

Corrected UGR values (at 2100 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		viewed crosswise					viewed endwise				
		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
2H	2H	17.6	18.3	17.9	18.5	18.8	17.6	18.3	17.9	18.5	18.8
	3H	17.5	18.1	17.8	18.4	18.6	17.5	18.1	17.8	18.4	18.6
	4H	17.4	18.0	17.8	18.3	18.6	17.4	18.0	17.8	18.3	18.6
	6H	17.3	17.9	17.7	18.2	18.5	17.3	17.9	17.7	18.2	18.5
	8H	17.3	17.8	17.7	18.1	18.5	17.3	17.8	17.7	18.1	18.5
	12H	17.3	17.7	17.7	18.1	18.4	17.3	17.7	17.7	18.1	18.4
4H	2H	17.4	18.0	17.8	18.3	18.6	17.4	18.0	17.8	18.3	18.6
	3H	17.3	17.7	17.7	18.1	18.4	17.3	17.7	17.7	18.1	18.4
	4H	17.2	17.6	17.6	18.0	18.3	17.2	17.6	17.6	18.0	18.3
	6H	17.1	17.5	17.5	17.9	18.3	17.1	17.5	17.5	17.9	18.3
	8H	17.1	17.4	17.5	17.8	18.2	17.1	17.4	17.5	17.8	18.2
	12H	17.0	17.3	17.5	17.7	18.2	17.0	17.3	17.5	17.7	18.2
8H	4H	17.1	17.4	17.5	17.8	18.2	17.1	17.4	17.5	17.8	18.2
	6H	17.0	17.2	17.4	17.7	18.1	17.0	17.2	17.4	17.7	18.1
	8H	16.9	17.1	17.4	17.6	18.1	16.9	17.1	17.4	17.6	18.1
	12H	16.9	17.1	17.4	17.5	18.1	16.9	17.1	17.4	17.5	18.1
12H	4H	17.0	17.3	17.5	17.7	18.2	17.0	17.3	17.5	17.7	18.2
	6H	16.9	17.1	17.4	17.6	18.1	16.9	17.1	17.4	17.6	18.1
	8H	16.9	17.1	17.4	17.5	18.1	16.9	17.1	17.4	17.5	18.1
Variations with the observer position at spacing:											
S =	1.0H	4.4 / -24.6					4.4 / -24.6				
	1.5H	7.2 / -25.8					7.2 / -25.8				
	2.0H	9.2 / -26.2					9.2 / -26.2				