

Palco Low Voltage

Design Artec
Studio

iGuzzini

Last information update: March 2025

Product configuration: Q648.01+GOBO4

Q648.01: Palco LV spotlight Ø 19 - Framer - 3.4W 3.8lm - 3000K - CRI 90 - White
GOBO4: Gobo ø4 mm



Product code

Q648.01: Palco LV spotlight Ø 19 - Framer - 3.4W 3.8lm - 3000K - CRI 90 - White

Technical description

Miniaturised adjustable projector spotlight with adapter for installation on 48V low voltage track. The adapter made of a thermoplastic material includes the DC/DC driver circuit with a DALI dimmable function. Technical body for LED lamp made of die-cast zamak; high definition reflector. The aluminium optical assembly includes a sophisticated telecentric optic system consisting of four anti-reflection treated glass lenses. Black anodised aluminium locknut for manual focusing. The innovative optic system, combined with the option of manual adjustment provides sharp and precise wall illumination with no halo effects or soft edges. The optical assembly is secured to the technical body with a rapid and practical magnetic system; this solution allows the unit to be rotated by 360° which considerably increases its versatility. The spotlight is designed to obtain a circular-shaped emission: a gobo with different projection diameters is included in the package. A rapid tool-free system for connecting the adapter electrically and mechanically to the track.

Installation

Mechanical fastening with adapter on track.

Colour

White (01)

Weight (Kg)

0.08

Mounting

Low voltage track

Wiring

Integrated DC/DC LED driver in adapter - direct connection on 48V track. Track power supply unit to be ordered separately.

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	13	MacAdam Step:	2
W system:	2	Lamp code:	LED
Im source:	190	Number of lamps for optical assembly:	1
W source:	2	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	6.7	Number of optical assemblies:	1
Im in emergency mode:	-	LED current [mA]:	700
Total light flux at or above an angle of 90° [Lm]:	0	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	7	Minimum dimming %:	5
CRI (minimum):	90	Overvoltage protection:	2kV Common mode & 1kV Differential mode
Colour temperature [K]:	3000	Control:	DALI

Polar

