


Last information update: April 2025

Product configuration: QA46

QA46: Fixed round recessed luminaire - Minimal - medium - Super Comfort

**Product code**

QA46: Fixed round recessed luminaire - Minimal - medium - Super Comfort

Technical description

Minimal round recessed luminaire (frameless). Super Comfort fixed version: the LEDs are set a long way back to minimize glare and guarantee a high level of visual comfort. The main body is made of die-cast aluminium with a radiant surface that guarantees optimum heat dissipation. Metallised, thermoplastic, high definition reflector - medium optic. Die-cast aluminium structure designed for flush with ceiling installation - a specific adapter with a separate code is available for false ceilings. This is indispensable for installing recessed luminaires. The internal ring is made of thermoplastic available in a range of painted and metallised finishes. Safety glass included LED lamp with high color rendering index. Power unit available with a separate code no.

Installation

The luminaire is recessed in the adapter (QA80) by means of an anti-fall steel wire spring, previously installed on the ceiling that can be between 12.5 and 25 mm thick. A special steel spring required to extract the main body of the adapter after it has been installed is included in the package.

Colour

White (01) | Black (04) | Chrome (10)* | Gold (14)* | Burnished chrome (E6)* | Gold satin-finish (E8)*

Weight (Kg)

0.1

* Colours on request

Mounting

ceiling recessed

Wiring

Direct current ballasts are available with a separate code no.: ON-OFF / 1-10V dimmable / DALI dimmable / Trailing Edge dimmable - the recessed fitting includes a cable and a quick-coupling connector to connect it to the connector on the ballast.

Notes

A wide range of decorative accessories and diffusers is available.

Complies with EN60598-1 and pertinent regulations



IP20

**Technical data**

Im system:	616	CRI (minimum):	90
W system:	6.8	Colour temperature [K]:	2700
Im source:	760	MacAdam Step:	2
W source:	6.8	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	90.5	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	81	Number of optical assemblies:	1
Beam angle [°]:	22°	LED current [mA]:	200


Polar

Imax=3256 cd		CIE		Lux			
		nL 0.81 100-100-100-100-81 UGR <10-10 DIN A.61 UTE 0.81A+0.00T F*1=1000 F*1+F*2=1000 F*1+F*2+F*3=1000 CIBSE LG3 L<1500 cd/m² at 65° UGR<10 L<1500 cd/mq @65°		h	d	Em	Emax
				2	0.8	682	814
				4	1.6	171	204
				6	2.4	76	90
				8	3.2	43	51

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	73	70	67	65	69	66	66	64	78
1.0	76	73	71	69	72	70	70	67	83
1.5	80	78	76	74	77	75	74	72	89
2.0	83	81	79	78	80	78	78	75	93
2.5	84	83	82	81	82	81	80	78	96
3.0	85	84	83	83	83	82	81	79	98
4.0	86	85	85	84	84	84	82	81	99
5.0	87	86	86	86	85	84	83	81	100

Luminance curve limit



UGR diagram

Corrected UGR values (at 700 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		viewed crosswise					viewed endwise				
2H	2H	-10.4	-8.3	-10.0	-7.9	-7.6	-10.4	-8.3	-10.0	-7.9	-7.6
	3H	-10.6	-8.9	-10.2	-8.6	-8.3	-10.6	-8.9	-10.2	-8.6	-8.3
	4H	-10.6	-9.3	-10.2	-9.0	-8.6	-10.6	-9.3	-10.2	-9.0	-8.6
	6H	-10.7	-9.7	-10.3	-9.4	-9.0	-10.6	-9.7	-10.3	-9.3	-9.0
	8H	-10.7	-9.7	-10.3	-9.4	-9.0	-10.7	-9.7	-10.3	-9.4	-9.0
	12H	-10.8	-9.8	-10.4	-9.4	-9.0	-10.7	-9.8	-10.3	-9.4	-9.0
4H	2H	-10.6	-9.3	-10.2	-9.0	-8.6	-10.6	-9.3	-10.2	-9.0	-8.6
	3H	-10.7	-9.8	-10.3	-9.4	-9.0	-10.7	-9.8	-10.3	-9.4	-9.0
	4H	-10.9	-9.9	-10.5	-9.5	-9.1	-10.9	-9.9	-10.5	-9.5	-9.1
	6H	-11.3	-9.5	-10.8	-9.1	-8.6	-11.3	-9.5	-10.8	-9.1	-8.6
	8H	-11.4	-9.4	-10.9	-9.0	-8.5	-11.4	-9.4	-10.9	-9.0	-8.5
	12H	-11.5	-9.5	-11.0	-9.0	-8.5	-11.5	-9.5	-11.0	-9.0	-8.5
8H	4H	-11.4	-9.4	-10.9	-9.0	-8.5	-11.4	-9.4	-10.9	-9.0	-8.5
	6H	-11.5	-9.7	-11.0	-9.2	-8.7	-11.5	-9.7	-11.0	-9.2	-8.7
	8H	-11.5	-9.9	-11.0	-9.4	-8.9	-11.5	-9.9	-11.0	-9.4	-8.9
	12H	-11.4	-10.3	-10.8	-9.8	-9.3	-11.4	-10.3	-10.8	-9.8	-9.3
12H	4H	-11.5	-9.5	-11.0	-9.0	-8.5	-11.5	-9.5	-11.0	-9.0	-8.5
	6H	-11.5	-9.9	-11.0	-9.4	-8.9	-11.5	-9.9	-11.0	-9.4	-8.9
	8H	-11.4	-10.3	-10.8	-9.8	-9.3	-11.4	-10.3	-10.8	-9.8	-9.3
Variations with the observer position at spacing:											
S =		1.0H					5.8 / -10.9				
		1.5H					8.6 / -24.0				
		2.0H					10.6 / -25.0				