

Last information update: November 2024

### Product configuration: QB23+QZ62.01

QB23: Down LO plate - DALI - General Light - LED Warm - L 3588

QZ62.01: Module for continuous line - Minimal Down - General Light - L 3596 - TP(a) - White

### Product code

QB23: Down LO plate - DALI - General Light - LED Warm - L 3588

### Technical description

LED module set up for housing in intermediate system profiles, ideal for particularly long light lines. Down emission - Low Output version for General Light profiles (with opal diffuser screen). DALI dimmable control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm 3000K LED

### Installation

Module insertion on profiles facilitated by a quick coupling system.

### Colour

Indeterminate (00)

### Weight (Kg)

3.8

### Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable DALI control gear.

### Notes

Important: the triple length intermediate luminous module can be used for both initial profiles - L 3594 - for stand-alone applications, and intermediate profiles - L 3594 - for continuous line applications.

Complies with EN60598-1 and pertinent regulations



### Product code

QZ62.01: Module for continuous line - Minimal Down - General Light - L 3596 - TP(a) - White

### Technical description

Extruded aluminium intermediate profile - Minimal (frameless) version for flush with ceiling mounting; this allows continuous lines to be created with other intermediate profiles and an initial profile (required). Polycarbonate screen for diffused general light in compliance with the TP(a) standard; screen set up for connecting different lengths by overlapping.

### Installation

Installation can be recessed, surface, ceiling and pendant-mounted using suitable accessories to be ordered separately; the mechanical systems for connecting the subsequent profiles are included in the package.

### Colour

White (01)

### Weight (Kg)

7

### Mounting

ceiling recessed|ceiling surface|ceiling pendant

### Wiring

Set up exclusively to house L 3588 triple-length LED modules.

### Notes


Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

Complies with EN60598-1 and pertinent regulations



### Technical data

lm system:	4788	CRI (minimum):	80
W system:	45	Colour temperature [K]:	3000
lm source:	7600	MacAdam Step:	3
W source:	45	Lamp code:	LED
Luminous efficiency (lm/W, real value):	106.4	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	63	Control:	DALI-2



Polar

