

Last information update: November 2024

Product configuration: QB30+QA96.01

QB30: Up / Down LO plate - DALI - General Light - LED Warm - L 1196

QA96.01: Initial module - Minimal Up / Down - General Light - L 1208 - White

Product code

QB30: Up / Down LO plate - DALI - General Light - LED Warm - L 1196

Technical description

LED module set up for housing in initial or intermediate system profiles. Up + down emission - Low Output version for General Light profiles (with lower opal diffuser screen). DALI dimmable control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm 3000K LED

Installation

Module insertion on profiles facilitated by a quick coupling system.

Colour

Indeterminate (00)

Weight (Kg)

1.6

Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable digital DALI control gear.

Complies with EN60598-1 and pertinent regulations

**Product code**

QA96.01: Initial module - Minimal Up / Down - General Light - L 1208 - White

Technical description

Initial profile in extruded aluminium - Minimal (frameless) version for flush with ceiling mounting available for direct and indirect lighting (luminous flux split into approx. 70% down / 30% up.); methacrylate opal lower screen for diffused general light; screen set up for connecting several lengths by overlapping. Methacrylate diffusing screen for upper emission.

Installation

Installation can be pendant-mounted using suitable accessories to be ordered separately. The initial modules can be used individually for various applications if completed with accessory caps and the required LED module.

Colour

White (01)

Weight (Kg)

2.35

Mounting

ceiling pendant

Wiring

Set up to house the LED modules required by the system.

Notes

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system: 2660

W system: 22

lm source: 3800

W source: 22

Luminous efficiency (lm/W, real value): 120.9

lm in emergency mode: -

Total light flux at or above an angle of 90° [Lm]: 752

Light Output Ratio (L.O.R.) [%]: 70

CRI (minimum): 80

Colour temperature [K]: 3000

MacAdam Step: 3


Lamp code: LED

Number of lamps for optical assembly: 1

ZVEI Code: LED

Number of optical assemblies: 1

Control: DALI-2



Polar

