

## Palco Recessed / Surface

Design Artec  
Studio

iGuzzini

Last information update: May 2025

### Product configuration: QC14

QC14: Palco linear recess 2 x Ø19 - medium - remote driver

### Product code

QC14: Palco linear recess 2 x Ø19 - medium - remote driver **Attention! Code no longer in production**

### Technical description

Linear luminaire for recessed installation with 2 miniaturised adjustable spotlights. Spotlight bodies with a cast zamak dissipation system and rotation units - a linear recess structure consisting of an extruded aluminium internal profile, painted steel caps and stop plate - steel wire fixing springs. The spotlight swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic units guarantees a high level of visual comfort with thermoplastic high definition lenses. Ballast not included, available with separate code.

### Installation

Recessed linear base with surface stop plate - steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 00 x 00 mm. Option of installing next to linear versions so as to create a continuous line.

### Colour

White (01) | Black (04)

### Weight (Kg)

0.17

### Mounting

wall recessed/ceiling recessed


### Wiring

Output cables for connecting to power supply line.

Complies with EN60598-1 and pertinent regulations



IP20



### Technical data

Im system:	255	CRI (minimum):	90
W system:	4	Colour temperature [K]:	3000
Im source:	190	MacAdam Step:	2
W source:	2	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	63.7	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical 1 assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	67	Number of optical assemblies:	2
Beam angle [°]:	24°	LED current [mA]:	700

### Polar

