

Palco Recessed / Surface

Last information update: February 2025

Product configuration: QC34
QC34: Palco single surface Ø19 - medium - remote driver



Product code
QC34: Palco single surface Ø19 - medium - remote driver

Technical description
Miniaturised adjustable spotlight for surface installation. Spotlight body with a cast zamak dissipation system and rotation unit - shaped steel fixing plate - thermoplastic surface cover base with stainless steel locking mechanism. The swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic unit guarantees a high level of visual comfort with a thermoplastic high definition lens. Ballast not included, available with separate code.


Installation
Installation surface plate fastening - spotlight unit attached to cover base with a locking mechanism.

| | |
|-------------------------|--------------------|
| Colour | Weight (Kg) |
| White (01) Black (04) | 0.06 |

Mounting
wall surface|ceiling surface

Wiring
Output cables for connecting to power supply line.

Complies with EN60598-1 and pertinent regulations



| Technical data | | | |
|--|------|---------------------------------------|---------------------------------|
| Im system: | 127 | CRI (minimum): | 90 |
| W system: | 2 | Colour temperature [K]: | 3000 |
| Im source: | 190 | MacAdam Step: | 2 |
| W source: | 2 | Life Time LED 1: | > 50,000h - L80 - B10 (Ta 25°C) |
| Luminous efficiency (Im/W, real value): | 63.7 | Lamp code: | LED |
| Im in emergency mode: | - | Number of lamps for optical assembly: | 1 |
| Total light flux at or above an angle of 90° [Lm]: | 0 | ZVEI Code: | LED |
| Light Output Ratio (L.O.R.) [%]: | 67 | Number of optical assemblies: | 1 |
| Beam angle [°]: | 24° | LED current [mA]: | 700 |

Polar

