



Product configuration: QK19.01
QK19.01: Minimal 1 cell - Wall Washer - LED - White



QK19.01: Minimal 1 cell - Wall Washer - LED - White

Recessed luminaire with fixed wall washer optic for LED lamp. Passive heat dissipation system. Lamp body with die-cast aluminium radiant surface, flush with ceiling version (frameless). For recessed installation in a false ceiling a specific adapter is required that is available with a separate item code. Specialised asymmetrical optic system designed to achieve a highly defined light distribution on walls and eliminate any shadow zones. Superpure aluminium reflector/flux enhancer - PMMA screen/refractor and thermoplastic holding structure. Supplied with a dimmable DALI electronic ballast connected to the luminaire.

The luminaire is recessed in the specific adapter (QK49) by means of a steel wire spring, previously installed on the ceiling that can be between 12.5 and 25 mm thick. To light walls correctly check the installation distances and centre-to-centre distances indicated on the instructions sheet.

Colour	Weight (Kg)
White (01)	0.48

ceiling recessed


Quick-coupling connections on the ballast unit. Digital electronic cabling that allows dimming to be performed with DALI protocol or a pushbutton switch (read the indications on the instruction sheet carefully).

Complies with EN60598-1 and pertinent regulations



Im system:	598	Colour temperature [K]:	4000
W system:	8.6	MacAdam Step:	2
Im source:	1050	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	6.5	Voltage [Vin]:	230
Luminous efficiency (lm/W, real value):	69.6	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	57	Number of optical assemblies:	1
CRI (minimum):	80	Control:	DALI-2

Polar



Illuminances

Lux												Wall distance = 1m	
3													
	0.9	2	6	20	57	86	57	20	6	2	0.9		
2	2	5	11	25	60	88	60	25	11	5	2		
	3	5	10	23	46	60	46	23	10	5	3		
1	3	5	9	18	31	37	31	18	9	5	3		
	2	4	8	14	20	23	20	14	8	4	2		
0													
	m	-2	-1	0	1	2	3						