


Last information update: April 2025

Product configuration: QL47

QL47: Minimal section 3 x 5 LEDs - Wall Washer

**Product code**

QL47: Minimal section 3 x 5 LEDs - Wall Washer

Technical description

Linear recessed miniaturised luminaire for LED lamps, specialised for vertical wall lighting. The patented optic system guarantees a homogeneous and effective emission on the wall, as well as avoiding shadow zones near the ceiling. Main body with die-cast aluminium radiant surface, minimal (frameless) version for mounting flush with the ceiling. For recessed installation in a false ceiling a specific adapter is required that is available with a separate item code. Flux enhancer - superpure aluminium reflector - asymmetrical textured PMMA screen - black polycarbonate internal perimeter frame. Supplied with a power supply unit connected to the luminaire. High colour rendering LED.

Installation

The recess body is inserted in the specific adapter installed previously by means of a steel wire spring - check the thickness of the false ceiling and use a compatible frame available with a separate item code.

Colour

Black (04)

Weight (Kg)


0.85

Mounting

wall recessed|ceiling recessed

Wiring

on power supply box: screw connections.



Complies with EN60598-1 and pertinent regulations

**Technical data**

| | | | |
|--|-----------|---------------------------------------|------------------------------|
| lm system: | 994.25 | CRI: | 95 |
| W system: | 35.0 | Colour temperature [K]: | 2700 |
| lm source: | 2550 | MacAdam Step: | 3 |
| W source: | 31 | Life Time LED 1: | 50,000h - L90 - B10 (Ta 25C) |
| Luminous efficiency (lm/W, real value): | 28.41 | Lamp code: | LED |
| lm in emergency mode: | - | Number of lamps for optical assembly: | 1 |
| Total light flux at or above an angle of 90° [Lm]: | 0.0 | ZVEI Code: | LED |
| Light Output Ratio (L.O.R.) [%]: | 39 | Number of optical assemblies: | 1 |
| Beam angle [°]: | 50° / 64° | Control: | DALI-2 |