

Last information update: March 2025

**Product configuration: QL74**

QL74: Ø597mm - warm white - Opal - DALI



**Product code**

QL74: Ø597mm - warm white - Opal - DALI

**Technical description**

Round luminaire for ceiling-mounted installation with option of recessed or pendant installation via an accessory to be ordered separately. Up/down emission designed to use warm white 3000K LED lamps. The optical assembly consists of an extruded painted aluminium frame, a satin finish methacrylate diffuser screen for general light emission and a sheet metal rear closing base. The driver is housed in the upper part of the product.

**Installation**

Ceiling-mounted. Recessed or pendant-mounted using an accessory to be ordered separately.

**Colour**

White (01) | Black (04)

**Weight (Kg)**

6.5

**Mounting**

wall surface/ceiling surface

**Wiring**

Product complete with electronic components. The electrical cables used are made of a "halogen free" material. (This means that the cables do not contain any halogen materials that in the event of a fire do not emit toxic or corrosive gases and only a small quantity of opaque fumes).

Complies with EN60598-1 and pertinent regulations



**Technical data**

|  |       |                                       |                               |
|--|-------|---------------------------------------|-------------------------------|
| lm system:   | 5421  | Colour temperature [K]:               | 3000                          |
| W system:  | 43.1  | MacAdam Step:                         | 3                             |
| lm source:   | 6950  | Life Time LED 1:                      | 50,000h - L90 - B10 (Ta 25°C) |
| W source:  | 39    | Lamp code:                            | LED                           |
| Luminous efficiency (lm/W, real value):            | 125.8 | Number of lamps for optical assembly: | 1                             |
| lm in emergency mode:                              | -     | ZVEI Code:                            | LED                           |
| Total light flux at or above an angle of 90° [Lm]: | 160   | Number of optical assemblies:         | 1                             |
| Light Output Ratio (L.O.R.) [%]:                   | 78    | Control:                              | DALI-2                        |
| CRI (minimum):                                     | 80    |                                       |                               |

**Polar**

