


Last information update: March 2025

Product configuration: QL79

QL79: Ø1157mm - Neutral White - Opal - DALI



Product code

QL79: Ø1157mm - Neutral White - Opal - DALI

Technical description

Round luminaire for ceiling-mounted installation with option of recessed or pendant installation via an accessory to be ordered separately. Up/down emission designed to use Neutral White 4000K LED lamps. The optical assembly consists of an extruded painted aluminium frame, a satin finish methacrylate diffuser screen for general light emission and a sheet metal rear closing base. The driver is housed in the upper part of the product.

Installation

Ceiling-mounted. Recessed or pendant-mounted using an accessory to be ordered separately.

Colour

White (01) | Black (04)

Weight (Kg)

20

Mounting

wall surface|ceiling surface

Wiring

Product complete with electronic components. The electrical cables used are made of a "halogen free" material. (This means that the cables do not contain any halogen materials that in the event of a fire do not emit toxic or corrosive gases and only a small quantity of opaque fumes).

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	22854	Colour temperature [K]:	4000
W system:	167.6	MacAdam Step:	3
Im source:	29300	Life Time LED 1:	50,000h - L90 - B10 (Ta 25°C)
W source:	156	Lamp code:	LED
Luminous efficiency (lm/W, real value):	136.4	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	370	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	78	Control:	DALI-2
CRI (minimum):	80		

Polar

