

## Palco Low Voltage


Design Artec  
Studio

iGuzzini

Last information update: May 2025

### Product configuration: QP10.01

QP10.01: Palco LV spotlight Ø 62 - Medium beam - 19.5W 1677lm - 3000K - CRI 90 - White



### Product code

QP10.01: Palco LV spotlight Ø 62 - Medium beam - 19.5W 1677lm - 3000K - CRI 90 - White

### Technical description

Adjustable spotlight with adapter for installation on 48V low voltage track. Made of die-cast aluminium with passive dissipation system. The adapter made of a thermoplastic material includes the DC/DC driver circuit with a DALI dimmable function. Integrated «power line» technology allows each spotlight on the track to be adjusted separately. The swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic unit guarantees a high level of visual comfort. Superpure aluminium reflector with high definition OPTI BEAM technology. A rapid tool-free system for connecting the adapter electrically and mechanically to the track.

### Installation

Mechanical fastening with adapter on track.

### Colour

White (01)

### Weight (Kg)

0.41

### Mounting

Low voltage track

### Wiring

Integrated DC/DC LED driver in adapter - direct connection on 48V track. Track power supply unit to be ordered separately.

### Notes

Technical and anti-glare accessories available; with option of the combined installation of two internal accessories.


Complies with EN60598-1 and pertinent regulations



### Technical data

lm system:	1677	MacAdam Step:	2
W system:	19.5	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
lm source:	2150	Voltage [Vin]:	48
W source:	18	Lamp code:	LED
Luminous efficiency (lm/W, real value):	86	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	78	LED current [mA]:	520
Beam angle [°]:	26°	Power factor:	See installation instructions
CRI (minimum):	90	Minimum dimming %:	5
Rf (Colour Fidelity Index):	92	Overvoltage protection:	2kV Common mode & 1kV Differential mode
Rg (Gamut Index):	99	Dimming mode:	CCR
Colour temperature [K]:	3000	Control:	DALI

### Polar

I <sub>max</sub> =7556 cd		Lux			
		h	d	Em	Emax
		1	0.5	6080	7556
		2	0.9	1520	1889
		3	1.4	676	840
		4	1.8	380	472
α = 26°					

# Isolux

