

Palco Low Voltage


Design Artec
Studio

iGuzzini

Last information update: May 2025

Product configuration: QP14.01

QP14.01: Palco LV spotlight Ø 62 - Flood beam - 19.5W 1619.5lm - 2700K - CRI 90 - White



Product code

QP14.01: Palco LV spotlight Ø 62 - Flood beam - 19.5W 1619.5lm - 2700K - CRI 90 - White

Technical description

Adjustable spotlight with adapter for installation on 48V low voltage track. Made of die-cast aluminium with passive dissipation system. The adapter made of a thermoplastic material includes the DC/DC driver circuit with a DALI dimmable function. Integrated «power line» technology allows each spotlight on the track to be adjusted separately. The swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic unit guarantees a high level of visual comfort. Superpure aluminium reflector with high definition OPTI BEAM technology. A rapid tool-free system for connecting the adapter electrically and mechanically to the track.

Installation

Mechanical fastening with adapter on track.

Colour

White (01)

Weight (Kg)

0.41

Mounting

Low voltage track

Wiring

Integrated DC/DC LED driver in adapter - direct connection on 48V track. Track power supply unit to be ordered separately.

Notes

Technical and anti-glare accessories available; with option of the combined installation of two internal accessories.


Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	1620	MacAdam Step:	2
W system:	19.5	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Im source:	2050	Voltage [Vin]:	48
W source:	18	Lamp code:	LED
Luminous efficiency (Im/W, real value):	83.1	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	79	LED current [mA]:	520
Beam angle [°]:	42°	Power factor:	See installation instructions
CRI (minimum):	90	Minimum dimming %:	5
Rf (Colour Fidelity Index):	92	Overvoltage protection:	2kV Common mode & 1kV Differential mode
Rg (Gamut Index):	99	Dimming mode:	CCR
Colour temperature [K]:	2700	Control:	DALI

Polar



Illuminances

