


Product configuration: QP42.43

QP42.43: Ø75 Deco - Pendant system for 48V track - Medium Beam - 15.3W 1336.5lm - 2700K - CRI 90 - Black / Black



QP42.43: Ø75 Deco - Pendant system for 48V track - Medium Beam - 15.3W 1336.5lm - 2700K - CRI 90 - Black / Black

Ø75 mm decorative cylindrical pendant system including an adapter for installation on 48V low voltage track ideal for zenithal accent lighting. The adapter includes the DC/DC driver circuit with a DALI dimmable function. Integrated «power line» technology allows each light module on the track to be adjusted separately. Fixed optic lighting system with a high definition reflector made of metallised thermoplastic. A decorative terminal element - in thick transparent PMMA - emphasises and elegantly defines light diffusion. Structural cylinder made of painted extruded aluminium with an inner ring made of black thermoplastic. Glass cover PVC power/pendant cable that can be cut to the required length, in the same colour as the external finish. Tool-free electrical and mechanical adapter connection to the track with a tear-proof safety device.

Mechanical fastening with adapter on track.

Colour
Black / Black (43)

Weight (Kg)
0.67

ly track pendant

Integrated DC/DC LED driver in adapter - direct connection on 48V track- track power unit to be ordered separately. The pendant cable can be adjusted on the pendant body.

Complies with EN60598-1 and pertinent regulations



| | | | |
|--|------|---------------------------------------|---|
| Im system: | 1337 | Life Time LED 1: | > 50,000h - L90 - B10 (Ta 25°C) |
| W system: | 15.3 | Voltage [Vin]: | 48 |
| Im source: | 1650 | Lamp code: | LED |
| W source: | 14 | Number of lamps for optical assembly: | 1 |
| Luminous efficiency (lm/W, real value): | 87.4 | ZVEI Code: | LED |
| Im in emergency mode: | - | Number of optical assemblies: | 1 |
| Total light flux at or above an angle of 90° [Lm]: | 0 | Power factor: | See installation instructions |
| Light Output Ratio (L.O.R.) [%]: | 81 | Minimum dimming %: | 5 |
| Beam angle [°]: | 28° | Overvoltage protection: | 2kV Common mode & 1kV Differential mode |
| CRI (minimum): | 90 | Dimming mode: | CCR |
| Colour temperature [K]: | 2700 | Control: | DALI |
| MacAdam Step: | 2 | | |

I_{max}=5700 cd
CIE
 nL 0.81
 99-99-100-100-81
 UGR <10-<10
DIN
 A.61
UTE
 0.81 A+0.00 T
 F"1=987
 F"1+F"2=993
 F"1+F"2+F"3=998
CIBSE
 LG3 L<1500 cd/m² at 65°
 UGR<10 | L<1500 cd/mq @