



Design iGuzzini

Last information update: May 2025

QW75.43: 5-cell recessed luminaire - LED - Warm White - Wide Oval - longitudinal optic - 12.7W 756lm - 2700K - CRI 90 - Black / Black



QW75.43: 5-cell recessed luminaire - LED - Warm White - Wide Oval - longitudinal optic - 12.7W 756lm - 2700K - CRI 90 - Black / Black

Rectangular miniaturised recessed luminaire with 5 optical elements fitted with LED lamps - fixed Wide Oval optics - wide opening asymmetrical emission with a longitudinal effect. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen. Supplied with DALI dimmable control gear unit connected to the luminaire.

recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 37 x 141

Black / Black (43)

0.3

wall recessed|ceiling recessed

on control gear box: screw connections with terminal block included

Complies with EN60598-1 and pertinent regulations



lm system:	756	CRI (typical):	92
W system:	12.7	Colour temperature [K]:	2700
lm source:	1050	MacAdam Step:	3
W source:	9.9	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	59.5	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	72	Number of optical assemblies:	1
CRI (minimum):	90	Control:	DALI-2

I_{max}=722 cd
C90-270
CIE
 nL 0.72
 83-99-100-100-72
 UGR 15.6-25.2
DIN
 A.61
UTE
 0.72B+0.00T
 F"1=835
 F"1+F"2=994
 F"1+F"2+F"3=1000
CIBSE
 LG3 L<3000 cd/m² at 65°
 UGR<16 | L<3000 cd/mq @