



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2022011001485140

Valid from: Jul.21,2022

Valid until: Jul.20,2027

NAME AND REGISTERED ADDRESS OF THE APPLICANT iGuzzini illuminazione S.p.A.
Via Mariano Guzzini, 37 62019 Recanati, Italy

NAME AND REGISTERED ADDRESS OF THE MANUFACTURER iGuzzini illuminazione S.p.A.
Via Mariano Guzzini, 37 62019 Recanati, Italy

NAME AND LOCATION OF THE FACTORY iGuzzini illuminazione S.p.A.
Via Mariano Guzzini, 37 62019 Recanati, Italy

PRODUCT MODEL(S) Fixed Luminaires For LED Modules (Ceiling Mounted, Controlled Port Dimming, A.C. Supplied
Electronic Controlgear For LED Modules, ClassII, IP20, Suitable For Direct Mounting On Normally
Flammable Surfaces)
See Appendix;220/240V ~ 50/60Hz.

STANDARDS AND TECHNICAL REQUIREMENTS GB/T 17743-2021;GB 7000.1-2015;GB 7000.201-2008

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C10-01:2014)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2022011001485140

page 1 of 1

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

控制端口调光 (DALI 调光) :

QY90 4.1W(12×0.24W/LED) , QY91 4.1W(12×0.24W/LED) , QY92 4.1W(12×0.24W/LED) ,
QY93 8.3W(24×0.24W/LED) , QY94 8.3W(24×0.24W/LED) , QY95 8.3W(24×0.24W/LED) ,
QY96 15.2W(48×0.24W/LED) , QY97 15.2W(48×0.24W/LED) , QY98 15.2W(48×0.24W/LED) ,
QZ02 8.3W(24×0.24W/LED) , QZ03 8.3W(24×0.24W/LED) , QZ04 8.3W(24×0.24W/LED) ,
QZ05 15.2W(48×0.24W/LED) , QZ06 15.2W(48×0.24W/LED) , QZ07 15.2W(48×0.24W/LED) ,
QZ11 13.3W(5×1.98W/LED) , QZ12 13.3W(5×1.98W/LED) , QZ13 13.3W(5×1.98W/LED) ,
QZ17 13.3W(5×1.98W/LED) , QZ18 13.3W(5×1.98W/LED) , QZ19 13.3W(5×1.98W/LED) ,
QZ20 21.5W(10×1.7W/LED) , QZ21 21.5W(10×1.7W/LED) , QZ22 21.5W(10×1.7W/LED) ,
YF53 21.5W(10×1.7W/LED) ,
QZ23 13.3W(5×1.98W/LED) , QZ24 13.3W(5×1.98W/LED) , QZ25 13.3W(5×1.98W/LED) ,
R650 6.8W(5×0.98W/LED) , R651 6.8W(5×0.98W/LED) , R652 6.8W(5×0.98W/LED) ,
R653 12.5W(10×0.98W/LED) , R654 12.5W(10×0.98W/LED) , R655 12.5W(10×0.98W/LED).
220/240V ~ 50/60Hz.



CHINA QUALITY CERTIFICATION CENTRE



中国国家强制性产品认证证书

证书编号: 2022011001485140

发证日期: 2022年07月21日

有效期至: 2027年07月20日

认证委托人名称 iGuzzini illuminazione S.p.A.
及注册地址 Via Mariano Guzzini, 37 62019 Recanati, 意大利

产品生产者名称 iGuzzini illuminazione S.p.A.
及注册地址 Via Mariano Guzzini, 37 62019 Recanati, 意大利

生产企业名称 iGuzzini illuminazione S.p.A.
及生产地址 Via Mariano Guzzini, 37 62019 Recanati, 意大利

产品名称和系列、规格、型号 固定式灯具 (吸顶式, 控制端口调光, LED 模块用交流电子控制装置, II 类, IP20, 适宜直接安装在普通可燃材料表面)
见附件; 220/240V ~ 50/60Hz。

产品标准和技术要求 GB/T 17743-2021; GB 7000.1-2015; GB 7000.201-2008

上述产品符合 CNCA-C10-01:2014 认证规则的要求, 特发此证。
证书有效期内本证书的有效性依据发证机构的定期监督获得保持。
经中国合格评定国家认可委员会认可 CNAS C001-P

可通过扫描下方二维码或登录国家认监委网站 (www.cnca.gov.cn) 查验证书信息



签发:

谢肇煦



中国质量认证中心



中国国家强制性产品认证证书

证书编号 2022011001485140

第 1 页 共 1 页

本证书及附件应同时使用，信息查验说明见证书页

纸号：

控制端口调光 (DALI 调光)：

QY90 4.1W(12×0.24W/LED)，QY91 4.1W(12×0.24W/LED)，QY92 4.1W(12×0.24W/LED)，
QY93 8.3W(24×0.24W/LED)，QY94 8.3W(24×0.24W/LED)，QY95 8.3W(24×0.24W/LED)，
QY96 15.2W(48×0.24W/LED)，QY97 15.2W(48×0.24W/LED)，QY98 15.2W(48×0.24W/LED)，
QZ02 8.3W(24×0.24W/LED)，QZ03 8.3W(24×0.24W/LED)，QZ04 8.3W(24×0.24W/LED)，
QZ05 15.2W(48×0.24W/LED)，QZ06 15.2W(48×0.24W/LED)，QZ07 15.2W(48×0.24W/LED)，
QZ11 13.3W(5×1.98W/LED)，QZ12 13.3W(5×1.98W/LED)，QZ13 13.3W(5×1.98W/LED)，
QZ17 13.3W(5×1.98W/LED)，QZ18 13.3W(5×1.98W/LED)，QZ19 13.3W(5×1.98W/LED)，
QZ20 21.5W(10×1.7W/LED)，QZ21 21.5W(10×1.7W/LED)，QZ22 21.5W(10×1.7W/LED)，
YF53 21.5W(10×1.7W/LED)，
QZ23 13.3W(5×1.98W/LED)，QZ24 13.3W(5×1.98W/LED)，QZ25 13.3W(5×1.98W/LED)，
R650 6.8W(5×0.98W/LED)，R651 6.8W(5×0.98W/LED)，R652 6.8W(5×0.98W/LED)，
R653 12.5W(10×0.98W/LED)，R654 12.5W(10×0.98W/LED)，R655 12.5W(10×0.98W/LED)。
220/240V ~ 50/60Hz。



中国质量认证中心