

Blade R downlight

Design iGuzzini

iGuzzini

Last information update: November 2024

Product configuration: R232

R232: Frame Ø 125 - Medium beam - LED



Product code

R232: Frame Ø 125 - Medium beam - LED

Technical description

Ring luminaire with 12 optical elements for LED lamps - fixed optics. The optic system guarantees a high level of visual comfort and no glare. The body includes a radiant surface made of die-cast aluminium. Version includes a perimeter surface frame. High definition reflectors made of thermoplastic material vacuum-metallised with aluminium vapours, integrated in a set-back position in the anti-glare screen. Supplied with a power supply unit connected to the luminaire.

Installation

Recessed with steel wire springs for false ceilings from 1 to 25 mm thick - Ø 125 installation hole.

Colour

White (01) | Black / Black (43) | Black / White (47) | White/Gold (41)* | White / burnished chrome (E7)*

Weight (Kg)

0.34

* Colours on request


Mounting

ceiling recessed

Wiring

On the power supply unit with terminal board included. Available in DALI versions.


Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	2094	CRI (minimum):	90
W system:	24	Colour temperature [K]:	4000
Im source:	2650	MacAdam Step:	2
W source:	24	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	87.2	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	79	Number of optical assemblies:	1
Beam angle [°]:	24°	Control:	DALI-2

Polar



Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	71	68	65	63	67	65	64	62	78
1.0	74	71	69	67	70	68	68	66	83
1.5	78	76	74	72	75	73	72	70	89
2.0	81	79	77	76	78	76	76	73	93
2.5	82	81	80	79	80	79	78	76	96
3.0	83	82	81	81	81	80	79	77	98
4.0	84	83	83	82	82	82	80	79	99
5.0	84	84	84	83	83	82	81	79	100

UGR diagram

Corrected UGR values (at 2050 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim											
x	y										
2H	2H	4.0	6.1	4.3	6.4	6.7	3.8	5.9	4.1	6.2	6.5
	3H	3.8	5.4	4.2	5.7	6.1	3.6	5.2	4.0	5.5	5.9
	4H	3.8	5.1	4.1	5.4	5.8	3.6	4.9	3.9	5.2	5.6
	6H	3.7	4.8	4.1	5.1	5.4	3.5	4.6	3.9	4.9	5.3
	8H	3.7	4.7	4.1	5.1	5.4	3.5	4.5	3.9	4.9	5.2
	12H	3.6	4.6	4.0	5.0	5.4	3.4	4.5	3.8	4.8	5.2
4H	2H	3.8	5.1	4.1	5.4	5.8	3.6	4.9	3.9	5.2	5.6
	3H	3.6	4.6	4.0	5.0	5.4	3.4	4.5	3.8	4.8	5.2
	4H	3.5	4.5	3.9	4.9	5.3	3.3	4.3	3.7	4.7	5.1
	6H	3.1	4.8	3.6	5.2	5.7	3.0	4.6	3.4	5.0	5.5
	8H	3.0	4.9	3.5	5.3	5.8	2.8	4.7	3.3	5.1	5.6
	12H	2.9	4.8	3.4	5.3	5.8	2.7	4.6	3.2	5.1	5.6
8H	4H	3.0	4.9	3.5	5.3	5.8	2.8	4.7	3.3	5.1	5.6
	6H	2.9	4.7	3.4	5.1	5.7	2.7	4.5	3.2	5.0	5.5
	8H	2.9	4.4	3.4	4.9	5.5	2.7	4.2	3.2	4.7	5.3
	12H	3.0	4.0	3.5	4.5	5.0	2.8	3.8	3.3	4.3	4.9
12H	4H	2.9	4.8	3.4	5.3	5.8	2.7	4.6	3.2	5.1	5.6
	6H	2.9	4.4	3.4	4.9	5.5	2.7	4.2	3.2	4.7	5.3
	8H	3.0	4.0	3.5	4.5	5.0	2.8	3.8	3.3	4.3	4.9
Variations with the observer position at spacing:											
S =		1.0H	6.6 / -40.0				6.7	/ -40.2			
		1.5H	8.0 / -54.2				7.8	/ -45.1			
		2.0H	8.8 / -53.4				8.6	/ -47.6			