

Last information update: May 2025

Product configuration: R480.D8

R480.D8: Ø 212 - 4000K - CRI80 - UGR<19 - DALI - White Transparent

**Product code**

R480.D8: Ø 212 - 4000K - CRI80 - UGR<19 - DALI - White Transparent

Technical description

Round fixed luminaire designed to use LED lamps with C.o.B. technology. Version with rim for surface-mounting. Prismatic thermoplastic reflector complete with flux enhancer. Optic available with two finishes, clear white or clear black. Dissipater made of painted grey die-cast aluminium. Product complete with LED lamp in neutral white colour tone (4000K) and microfilm that is able to guarantee a light beam of UGR<19 L<3000 cd/m², which is ideal for environments with video terminals.

Installation

Recessed using torsion springs which allow easy installation in false ceilings with thicknesses ranging from 1 mm to 25 mm.

Colour

White Transparent (D8)

Weight (Kg)

1.03

Mounting

ceiling surface

Wiring

Product complete with DALI components

Notes

TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations




IP20

IP54

On the visible part of the product once installed

**Technical data**


Im system:	2581	Colour temperature [K]:	4000
W system:	20.1	MacAdam Step:	2
Im source:	2900	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	17	Lamp code:	LED
Luminous efficiency (Im/W, real value):	128.4	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	89	Control:	DALI-2
CRI (minimum):	80		

Polar

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	72	65	61	58	64	60	60	56	63
1.0	77	71	67	64	70	66	66	62	69
1.5	83	79	76	73	78	75	74	70	79
2.0	87	84	81	79	82	80	79	76	85
2.5	89	87	84	83	85	83	82	79	89
3.0	91	89	87	85	87	85	84	81	91
4.0	92	90	89	88	89	88	86	83	94
5.0	93	92	90	89	90	89	87	85	95

Luminance curve limit



UGR diagram

Corrected UGR values (at 2900 lm bare lamp luminous flux)											
Riflect.: ceil/cav walls work pl. Room dim x y		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
		viewed crosswise					viewed endwise				
2H	2H	18.9	19.7	19.2	19.9	20.2	18.9	19.7	19.2	19.9	20.2
	3H	18.8	19.5	19.1	19.8	20.1	18.8	19.6	19.1	19.8	20.1
	4H	18.8	19.4	19.1	19.7	20.0	18.8	19.4	19.1	19.7	20.0
	6H	18.7	19.3	19.1	19.7	20.0	18.7	19.3	19.0	19.6	20.0
	8H	18.7	19.3	19.1	19.6	20.0	18.7	19.3	19.0	19.6	19.9
	12H	18.7	19.3	19.1	19.6	20.0	18.6	19.2	19.0	19.5	19.9
4H	2H	18.8	19.4	19.1	19.7	20.0	18.8	19.4	19.1	19.7	20.0
	3H	18.7	19.3	19.1	19.6	20.0	18.7	19.3	19.1	19.7	20.0
	4H	18.7	19.2	19.1	19.6	20.0	18.7	19.2	19.1	19.6	20.0
	6H	18.7	19.1	19.1	19.5	20.0	18.6	19.1	19.1	19.5	19.9
	8H	18.7	19.1	19.1	19.5	19.9	18.6	19.0	19.0	19.4	19.9
	12H	18.7	19.1	19.1	19.5	19.9	18.6	18.9	19.0	19.4	19.8
8H	4H	18.6	19.0	19.0	19.4	19.9	18.7	19.1	19.1	19.5	19.9
	6H	18.6	19.0	19.1	19.4	19.9	18.7	19.0	19.1	19.4	19.9
	8H	18.7	18.9	19.1	19.4	19.9	18.7	18.9	19.1	19.4	19.9
	12H	18.7	18.9	19.2	19.4	19.9	18.6	18.9	19.1	19.4	19.9
12H	4H	18.6	18.9	19.0	19.4	19.8	18.7	19.1	19.1	19.5	19.9
	6H	18.6	18.9	19.1	19.4	19.9	18.7	19.0	19.2	19.4	19.9
	8H	18.6	18.9	19.1	19.4	19.9	18.7	18.9	19.2	19.4	19.9
Variations with the observer position at spacing:											
S =	1.0H	1.6 / -3.0					1.6 / -3.0				
	1.5H	3.2 / -5.2					3.2 / -5.2				
	2.0H	5.0 / -6.5					5.0 / -6.5				