

Last information update: May 2025

### Product configuration: R532.83+QX48.01

R532.83: iN60 Space - LED module - L 1192 - DOWN emission - UGR < 19 - neutral - dimmable DALI - Transparent/Black  
QX48.01: iN60 MMO - Down Module - Minimal - L= 1192 - White



### Product code

R532.83: iN60 Space - LED module - L 1192 - DOWN emission - UGR < 19 - neutral - dimmable DALI - Transparent/Black

**Attention! Code no longer in production**

### Technical description

LED module designed to be housed in iN60 system profiles - downlight distribution - made up of an emission raster, lamp device and operating components. Version for UGR < 19 controlled luminance emission - in compliance with the standard for use in environments with video monitors. Translucent textured thermoplastic raster, created with a catadioptric system (patented Opti Beam Diamond optic) - with no galvanic treatments - combined with a PP cover with a gloss finish and an additional diffuser screen. The resulting optic system generates an extremely elegant and professional light emission. Integrated DALI dimmable driver.

### Installation

Module insertion on compartments with a mechanical easy-push system (steel snap-on springs).

### Colour

Black Transparent (83)


### Weight (Kg)

0.93

### Wiring

Quick coupling input terminal block connection. LED module complete with integrated DALI control gear. The electrical cables used are made of a "halogen free" material.

Complies with EN60598-1 and pertinent regulations



### Product code

QX48.01: iN60 MMO - Down Module - Minimal - L= 1192 - White **Attention! Code no longer in production**

### Technical description

The L profile=1192 mm is made of extruded aluminium. This is the Minimal version for down emission. The product can be used for recessed, surface-mounted and pendant applications, and for both stand alone and continuous line versions.

### Installation

It can be recessed using suitable accessories to be ordered separately. The modules are completed with end caps and rasters with LEDs to be ordered separately.

### Colour

White (01)


### Weight (Kg)

2

### Mounting

ceiling recessed|ceiling surface

Complies with EN60598-1 and pertinent regulations



### Technical data

lm system:	2520	Colour temperature [K]:	4000
W system:	21.9	MacAdam Step:	3
lm source:	3550	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	19	Lamp code:	LED
Luminous efficiency (lm/W, real value):	115.1	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	71	Control:	DALI-2
CRI (minimum):	90		

Polar

