

Last information update: May 2025

Product configuration: R554.83+QX52.01

R554.83: iN60 Space - LED module - L 1192 - settable UP / DOWN emission - General Light - neutral - Transparent/Black
 QX52.01: iN60 MMO - Up and Down Module - Minimal - L= 1192 - 4000K - CRI 90 - White

**Product code**

R554.83: iN60 Space - LED module - L 1192 - settable UP / DOWN emission - General Light - neutral - Transparent/Black

Attention! Code no longer in production

Technical description

LED module designed to be housed in iN60 system profiles - Up / Down light distribution in separate adjustment mode - made up of an emission raster, lamp device and operating components. Version for general light emission. UP: translucent shaped PC diffuser screen. DOWN: high efficiency emission with a translucent textured thermoplastic raster, created with a catadioptric system - with no galvanic treatments - combined with a PP cover with a gloss finish and an additional diffuser screen. The resulting optic system generates an extremely elegant and professional light emission. Option of adjusting up and down flows separately to obtain defined lighting. Integrated DALI dimmable driver.

Installation

Module insertion on compartments with a mechanical easy-push system (steel snap-on springs).

Colour

Black Transparent (83)


Weight (Kg)

0.93

Wiring

Quick coupling input terminal block connection. LED module complete with integrated DALI control gear. The electrical cables used are made of a "halogen free" material.

Complies with EN60598-1 and pertinent regulations

**Product code**

QX52.01: iN60 MMO - Up and Down Module - Minimal - L= 1192 - 4000K - CRI 90 - White **Attention! Code no longer in production**

Technical description

The L profile=1192 mm is made of extruded aluminium. This is the Minimal version for up (4000K and CRI90) and down emission. The product can be used for pendant applications; in both a stand alone version and when the product is used in continuous lines.

Installation

Installation can be pendant-mounted using suitable accessories to be ordered separately. The modules are completed with end caps and rasters with LEDs to be ordered separately.

Colour

White (01)


Weight (Kg)

2

Mounting

ceiling recessed|wall surface|ceiling pendant

Complies with EN60598-1 and pertinent regulations

**Technical data**

| | | | |
|--|-------|---------------------------------------|---------------------------------|
| lm system: | 5328 | Colour temperature [K]: | 4000 |
| W system: | 47.6 | MacAdam Step: | 3 |
| lm source: | 7400 | Life Time LED 1: | > 50,000h - L90 - B10 (Ta 25°C) |
| W source: | 41 | Lamp code: | LED |
| Luminous efficiency (lm/W, real value): | 111.9 | Number of lamps for optical assembly: | 1 |
| lm in emergency mode: | - | ZVEI Code: | LED |
| Total light flux at or above an angle of 90° [Lm]: | 1879 | Number of optical assemblies: | 1 |
| Light Output Ratio (L.O.R.) [%]: | 72 | Control: | DALI-2 |
| CRI (minimum): | 90 | | |

Polar

