



Last information update: May 2025

**Product configuration: RB39.74**

RB39.74: 5-cell recessed luminaire - LED - Warm White - Wide Oval - longitudinal optic - 12.7W 828lm - 3500K - CRI 90 - Grey / Black

**Product code**

RB39.74: 5-cell recessed luminaire - LED - Warm White - Wide Oval - longitudinal optic - 12.7W 828lm - 3500K - CRI 90 - Grey / Black

**Technical description**

Rectangular miniaturised recessed luminaire with 5 optical elements fitted with LED lamps - fixed Wide Oval optics - wide opening asymmetrical emission with a longitudinal effect. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen. Supplied with DALI dimmable control gear unit connected to the luminaire.

**Installation**

recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 37 x 141

**Colour**

Grey / Black (74)\*

**Weight (Kg)**

0.3

\* Colours on request

**Mounting**

wall recessed|ceiling recessed

**Wiring**

on control gear box; screw connections with terminal block included

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	828	CRI (typical):	92
W system:	12.7	Colour temperature [K]:	3500
lm source:	1150	MacAdam Step:	3
W source:	9.9	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	65.2	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	72	Number of optical assemblies:	1
CRI (minimum):	90	Control:	DALI-2

**Polar**