

Palco Low Voltage


Design Artec
Studio

iGuzzini

Last information update: April 2025

Product configuration: RC71

RC71: Palco LV spotlight Ø 51 - Wall Washer - Bluetooth



Product code

RC71: Palco LV spotlight Ø 51 - Wall Washer - Bluetooth

Technical description

Miniaturised adjustable spotlight with adapter for installation on 48V low voltage track. Made of die-cast aluminium with passive dissipation system. The adapter made of a thermoplastic material includes the DC/DC driver circuit and Bluetooth protocol. The swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. High definition lens in thermoplastic material. Asymmetric screen designed to create a homogeneous effect on walls from top to bottom and avoid shadow zones near the ceiling. A rapid tool-free system for connecting the adapter electrically and mechanically to the track. Luminaire with Bluetooth Low Energy technology (WiSilica). Frequency 2.4 GHz BLE. The luminaire can be controlled with the Quick BLE system and Smart Light Control app that enable on-off, dimming and scene recall functions. The app is available on the Apple Store and Google Play Store. It can be integrated in the system's "Mesh" network that allows multiple luminaires to be controlled. OTA (over the air) update via app. Integrated Beacon that can be activated via Smart Light Control (Eddystone, iBeacon, Alt Beacon) that enables functions including push notification and indoor navigation-wayfinding.

Installation

An adapter is used to fix the device mechanically and tool-free to the 48V track. Max luminaire-luminaire distance (*): 8 m; max smartphone-luminaire distance (*): 20 m.

Colour

White (01) | Black (04)

Weight (Kg)

0.29

Mounting

Low voltage track

Wiring

Direct connection on 48V track. Track power supply unit to be ordered separately. Luminaire can be controlled with Bluetooth technology (WiSilica)

Notes

To optimize vertical illumination consult the installation distance recommendations in the instructions sheet. (*) The maximum distance for Bluetooth installations is affected by physical obstacles, like walls, metal panels and the layout of the system. We suggest that a test is conducted at the installation site.

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	275.65	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
W system:	16.1	Voltage [Vin]:	48
Im source:	1450	Lamp code:	LED
W source:	15	Number of lamps for optical assembly:	1
Luminous efficiency (lm/W, real value):	17.12	ZVEI Code:	LED
Im in emergency mode:	-	Number of optical assemblies:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	LED current [mA]:	0.4
Light Output Ratio (L.O.R.) [%]:	19	Power factor:	See installation instructions
Beam angle [°]:	34° / 36°	Minimum dimming %:	1
CRI:	90	Overvoltage protection:	0kV Common mode & 0kV Differential mode
Colour temperature [K]:	3000	Control:	Bluetooth WiSilica
MacAdam Step:	2		