

Palco Low Voltage


Design Artec
Studio

iGuzzini

Last information update: May 2025

Product configuration: RC74

RC74: Palco LV spotlight Ø 86 - Wall Washer - Bluetooth



Product code

RC74: Palco LV spotlight Ø 86 - Wall Washer - Bluetooth **Attention! Code no longer in production**

Technical description

Adjustable spotlight with adapter for installation on 48V low voltage track. Made of die-cast aluminium with passive dissipation system. The adapter made of a thermoplastic material includes the DC/DC driver circuit and Bluetooth protocol. The swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. Superpure aluminium reflector with high definition OPTI BEAM technology. Asymmetric screen designed to create a homogeneous effect on walls from top to bottom and avoid shadow zones near the ceiling. A rapid tool-free system for connecting the adapter electrically and mechanically to the track. The 48V track coupling device is fitted with a mechanical anti-fall safety double block. Luminaire with Bluetooth Low Energy technology (WiSilica). Frequency 2.4 GHz BLE. The luminaire can be controlled with the Quick BLE system and Smart Light Control app that enable on-off, dimming and scene recall functions. The app is available on the Apple Store and Google Play Store. It can be integrated in the system's "Mesh" network that allows multiple luminaires to be controlled. OTA (over the air) update via app. Integrated Beacon that can be activated via Smart Light Control (Eddystone, iBeacon, Alt Beacon) that enables functions including push notification and indoor navigation-wayfinding.

Installation

An adapter is used to fix the device mechanically and tool-free to the 48V track. Max luminaire-luminaire distance (*): 8 m; max smartphone-luminaire distance (*): 20 m.

Colour

White (01) | Black (04)

Weight (Kg)

0.75

Mounting

Low voltage track

Wiring

Direct connection on 48V track. Track power supply unit to be ordered separately. Luminaire can be controlled with Bluetooth technology (WiSilica)

Notes

To optimize vertical illumination consult the installation distance recommendations in the instructions sheet. (*) The maximum distance for Bluetooth installations is affected by physical obstacles, like walls, metal panels and the layout of the system. We suggest that a test is conducted at the installation site.

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	1374	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W system:	26	Voltage [Vin]:	48
Im source:	3350	Lamp code:	LED
W source:	24	Number of lamps for optical 1 assembly:	
Luminous efficiency (lm/W, real value):	52.8	ZVEI Code:	LED
Im in emergency mode:	-	Number of optical assemblies:	1
Total light flux at or above an angle of 90° [Lm]:	0	LED current [mA]:	700
Light Output Ratio (L.O.R.) [%]:	41	Power factor:	See installation instructions
CRI (minimum):	90	Minimum dimming %:	1
Colour temperature [K]:	4000	Control:	Bluetooth WiSilica
MacAdam Step:	2		

Polar

Imax=1344 cd C0-180 γ=29°					Lux				
90°					h	d1	d2	Em	Emax
					2	2.5	2.2	196	276
					4	5.1	4.4	49	69
					6	7.6	6.7	22	31
					8	10.2	8.9	12	17
α=65° / 58°									

Isolux

