


Last information update: February 2025

Product configuration: RF77

RF77: Pendant Tecnica Evo - Ø117 body - Food Lighting - Fruit & Vegetables



Product code

RF77: Pendant Tecnica Evo - Ø117 body - Food Lighting - Fruit & Vegetables

Technical description

Pendant luminaire fitted with an adapter for installation on an electrified track. LED lamp with high color rendering index - specific, calibrated colour tones for highlighting vegetable products (fruit and vegetables). Die-cast aluminium luminaire. Optical system with high performance P.V.D. (Physical Vapour Deposition) anti-scratch aluminium reflector that offers an excellent light efficiency ratio. Flood emission angle. Balanced pendant system with double steel cable and adjustment system. Fitted with mechanical aiming locks, so rotation and tilting movements can be locked in position to ensure efficient light aiming even after the original installation or during maintenance. Integrated power supply unit. Designed to house other optical accessories in the Tecnica Evo range.

Installation

Installation on an electrified track.

Colour

White (01) | Black (04)

Weight (Kg)

1.48

Mounting

dali track

Wiring

Integrated power supply.

Complies with EN60598-1 and pertinent regulations



Technical data

lm system:	3367.0	MacAdam Step:	3
W system:	37.9	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25C)
lm source:	3700	Lamp code:	LED
W source:	34	Number of lamps for optical assembly:	1
Luminous efficiency (lm/W, real value):	88.84	ZVEI Code:	LED
lm in emergency mode:	-	Number of optical assemblies:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	91	Inrush current:	18 A / 250 µs
Beam angle [°]:	30°	Overvoltage protection:	0kV Common mode & 0kV Differential mode
CRI:	95	Control:	On/off
Colour temperature [K]:	3000		