

Easy Space Square





Design iGuzzini

iGuzzini

Last information update: April 2025

Product configuration: RI30.D8

RI30.D8: Square 105 - General Lighting - DALI - Neutral White - 11.2W 1518lm - 4000K - White Transparent



Product code

RI30.D8: Square 105 - General Lighting - DALI - Neutral White - 11.2W 1518lm - 4000K - White Transparent

Technical description

Square recess luminaire with fixed optics, in version with outer frame. High efficiency LED source for general lighting uses. Emission unit made up of a transparent PMMA prismatic reflector in combination with the flow recovery unit and diffuser screen, both produced in PMMA, integrated into the external polycarbonate structure. The painted die-cast aluminium diffuser encompasses the steel wire coupling springs. A DALI dimmer power supply unit connected to the luminaire.

Installation

recessed with steel wire springs for false ceilings from 1 to 25 mm thick

Colour

White Transparent (D8)

Weight (Kg)

0.35

Mounting

ceiling surface

Wiring

DALI dimmer functioning components included - power supply connection on the terminals with rapid connection of the driver.

Notes

TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations



IP20

IP54

On the visible part of
the product once installed



Technical data

lm system:	1518	Colour temperature [K]:	4000
W system:	11.2	MacAdam Step:	2
lm source:	1650	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	9.5	Lamp code:	LED
Luminous efficiency (lm/W, real value):	135.5	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	92	Control:	DALI-2
CRI (minimum):	80		


Polar

		CIE nL 0.92 78-95-99-100-92 UGR 21.9-21.6 DIN A.61 UTE 0.92B+0.00T F*1=776 F*1+F*2=952 F*1+F*2+F*3=988				
		Lux				
		h	d1	d2	Em	Emax
		1	1.3	1.3	862	1195
		2	2.6	2.6	216	299
		3	3.9	3.9	96	133
		4	5.2	5.2	54	75

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	73	67	62	59	66	62	61	57	62
1.0	79	73	68	65	71	67	67	63	68
1.5	85	81	77	74	79	76	75	71	78
2.0	89	86	83	80	84	82	81	77	84
2.5	92	89	86	84	87	85	84	81	88
3.0	93	91	89	87	89	88	86	83	90
4.0	95	93	92	90	91	90	89	85	93
5.0	96	94	93	92	93	91	90	87	94

Luminance curve limit



UGR diagram

Corrected UGR values (at 1050 lm bare lamp luminous flux)											
Reflect.: ceiling walls work pl. Room dim x y		viewed crosswise					viewed endwise				
2H	2H	21.1	21.9	21.4	22.2	22.4	21.1	21.9	21.4	22.2	22.4
	3H	21.3	22.0	21.6	22.3	22.6	21.2	21.9	21.5	22.2	22.5
	4H	21.4	22.1	21.7	22.4	22.7	21.1	21.8	21.5	22.1	22.4
	6H	21.5	22.1	21.8	22.4	22.8	21.1	21.7	21.4	22.0	22.4
	8H	21.5	22.1	21.9	22.5	22.8	21.1	21.7	21.4	22.0	22.4
	12H	21.5	22.1	21.9	22.5	22.8	21.0	21.6	21.4	22.0	22.3
4H	2H	21.2	21.8	21.5	22.1	22.5	21.4	22.1	21.7	22.4	22.7
	3H	21.4	22.0	21.8	22.3	22.7	21.5	22.1	21.9	22.5	22.8
	4H	21.6	22.1	22.0	22.5	22.9	21.6	22.1	22.0	22.5	22.9
	6H	21.8	22.2	22.2	22.6	23.1	21.6	22.1	22.0	22.5	22.9
	8H	21.9	22.3	22.3	22.7	23.1	21.6	22.0	22.0	22.4	22.9
	12H	21.9	22.3	22.4	22.8	23.2	21.6	22.0	22.0	22.4	22.8
8H	4H	21.6	22.0	22.0	22.4	22.9	21.9	22.3	22.4	22.7	23.2
	6H	21.9	22.2	22.4	22.7	23.2	22.0	22.4	22.5	22.8	23.3
	8H	22.0	22.3	22.5	22.8	23.3	22.1	22.4	22.6	22.9	23.4
	12H	22.2	22.5	22.7	22.9	23.5	22.1	22.4	22.6	22.9	23.4
12H	4H	21.6	21.9	22.0	22.4	22.8	22.0	22.4	22.5	22.8	23.3
	6H	21.9	22.2	22.4	22.7	23.2	22.2	22.5	22.7	22.9	23.4
	8H	22.1	22.3	22.6	22.8	23.3	22.3	22.5	22.8	23.0	23.5
Variations with the observer position at spacing:											
S =		1.0H					1.4 / -1.5				
		1.5H					2.2 / -2.6				
		2.0H					3.7 / -2.9				