

## Easy Space Square


Design iGuzzini

iGuzzini

Last information update: April 2025

### Product configuration: RI62.D8

RI62.D8: Square 225 - General Lighting - DALI - Warm White - White / transparent



### Product code

RI62.D8: Square 225 - General Lighting - DALI - Warm White - White / transparent

### Technical description

Square recess luminaire with fixed optics, in version with outer frame. High efficiency LED source - increased flow version to achieve maximum performance in general lighting uses. Emission unit made up of a transparent PMMA prismatic reflector in combination with the flow recovery unit and diffuser screen, both produced in PMMA, integrated into the external polycarbonate structure. The painted die-cast aluminium diffuser encompasses the steel wire coupling springs. A power supply unit connected to the luminaire.

### Installation

recessed with steel wire springs for false ceilings from 1 to 25 mm thick

### Colour

White Transparent (D8)

### Weight (Kg)

1.18

### Mounting

ceiling surface

### Wiring

DALI dimmer functioning components included - power supply connection on the terminals with rapid connection of the driver.

### Notes

TPa version available on request, contact iGuzzini for more info


Complies with EN60598-1 and pertinent regulations



### Technical data

Im system:	4257	Colour temperature [K]:	3000
W system:	32.8	MacAdam Step:	2
Im source:	4730	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	29	Lamp code:	LED
Luminous efficiency (Im/W, real value):	129.8	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	90	Control:	DALI-2
CRI (minimum):	80		


### Polar



# Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	69	61	56	52	60	56	55	50	56
1.0	74	68	63	59	66	62	62	57	63
1.5	82	77	73	70	76	72	71	67	75
2.0	86	82	79	77	81	78	77	73	81
2.5	89	86	83	81	84	82	81	77	86
3.0	90	88	86	84	86	84	83	80	88
4.0	92	90	88	87	88	87	85	82	91
5.0	93	91	90	88	89	88	87	83	93

# Luminance curve limit



# UGR diagram

Corrected UGR values (at 4730 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		viewed crosswise					viewed endwise				
2H	2H	21.2	22.1	21.5	22.4	22.6	21.2	22.1	21.5	22.4	22.6
	3H	21.2	22.0	21.5	22.3	22.6	21.4	22.2	21.7	22.5	22.8
	4H	21.2	21.9	21.5	22.2	22.6	21.3	22.1	21.7	22.4	22.7
	6H	21.2	21.9	21.5	22.2	22.5	21.2	21.9	21.6	22.3	22.6
	8H	21.2	21.9	21.6	22.2	22.5	21.2	21.9	21.6	22.2	22.6
	12H	21.2	21.8	21.6	22.2	22.5	21.2	21.8	21.6	22.2	22.5
4H	2H	21.3	22.1	21.7	22.4	22.7	21.2	21.9	21.5	22.2	22.6
	3H	21.3	22.0	21.7	22.3	22.7	21.4	22.0	21.7	22.3	22.7
	4H	21.3	21.9	21.7	22.3	22.7	21.3	21.9	21.7	22.3	22.7
	6H	21.4	21.9	21.8	22.3	22.7	21.3	21.8	21.7	22.2	22.6
	8H	21.4	21.9	21.9	22.3	22.7	21.3	21.7	21.7	22.1	22.6
	12H	21.4	21.8	21.9	22.3	22.7	21.2	21.6	21.7	22.1	22.5
8H	4H	21.3	21.7	21.7	22.1	22.6	21.4	21.8	21.8	22.3	22.7
	6H	21.4	21.7	21.8	22.2	22.7	21.4	21.8	21.9	22.2	22.7
	8H	21.4	21.7	21.9	22.2	22.7	21.4	21.7	21.9	22.2	22.7
	12H	21.5	21.8	22.0	22.2	22.8	21.4	21.7	21.9	22.2	22.7
12H	4H	21.2	21.6	21.7	22.1	22.5	21.4	21.8	21.9	22.2	22.7
	6H	21.3	21.7	21.8	22.1	22.6	21.4	21.7	21.9	22.2	22.7
	8H	21.4	21.7	21.9	22.2	22.7	21.4	21.7	21.9	22.2	22.7
Variations with the observer position at spacing:											
S =		1.0H				1.0 / -2.1				1.0 / -2.1	
		1.5H				2.1 / -4.8				2.1 / -4.9	
		2.0H				3.6 / -5.3				3.6 / -5.5	