


Last information update: April 2025

Product configuration: RM02.D8

RM02.D8: Ø 163 mm - warm white - DALI - 16.8W 2002lm - 3500K - CRI 90 - White Transparent

**Product code**

RM02.D8: Ø 163 mm - warm white - DALI - 16.8W 2002lm - 3500K - CRI 90 - White Transparent

Technical description

Round fixed luminaire designed to use LED lamps with C.o.B. technology. Version with rim for surface-mounting. Prismatic thermoplastic reflector complete with flux enhancer. Dissipater made of painted grey die-cast aluminium. Product complete with LED lamp in warm white colour tone (3500K). General lighting beam.

Installation

Recessed using torsion springs which allow easy installation in false ceilings with thicknesses ranging from 1 mm to 25 mm.

Colour

White Transparent (D8)

Weight (Kg)

0.76

Mounting

ceiling surface

Wiring

product complete with DALI components

Notes

TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations



IP20

IP54

On the visible part of the product once installed

**Technical data**

Im system:	2002	Colour temperature [K]:	3500
W system:	16.8	MacAdam Step:	2
Im source:	2200	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	15	Lamp code:	LED
Luminous efficiency (lm/W, real value):	119.2	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	91	Control:	DALI-2
CRI (minimum):	90		


Polar

Imax=2124 cd		CIE		Lux			
				h	d	Em	Emax
		nL 0.91 89-97-99-100-91 UGR 18.1-17.7 DIN A.61 UTE 0.91A+0.00T F*1=887 F*1+F*2=968 F*1+F*2+F*3=991		2	2.2	407	531
				4	4.3	102	133
				6	6.5	45	59
				8	8.6	25	33

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	77	72	68	65	71	68	67	64	70
1.0	82	77	73	71	76	73	72	69	75
1.5	87	83	80	78	82	79	79	75	83
2.0	90	88	85	83	86	84	83	80	88
2.5	92	90	88	87	89	87	86	83	91
3.0	94	92	91	89	90	89	88	85	94
4.0	95	94	93	92	92	91	90	87	96
5.0	96	95	94	93	93	92	91	88	97

Luminance curve limit



UGR diagram

Corrected UGR values (at 2200 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		viewed crosswise					viewed endwise				
2H	2H	17.0	17.7	17.3	18.0	18.2	17.0	17.7	17.3	18.0	18.2
	3H	17.2	17.9	17.5	18.2	18.4	17.0	17.6	17.3	17.9	18.2
	4H	17.4	18.0	17.7	18.3	18.6	16.9	17.6	17.3	17.9	18.2
	6H	17.6	18.2	17.9	18.5	18.8	16.9	17.5	17.3	17.8	18.1
	8H	17.7	18.2	18.0	18.5	18.9	16.9	17.4	17.2	17.8	18.1
	12H	17.7	18.3	18.1	18.6	19.0	16.8	17.4	17.2	17.7	18.1
4H	2H	16.9	17.6	17.3	17.9	18.2	17.4	18.0	17.7	18.3	18.6
	3H	17.3	17.8	17.7	18.2	18.5	17.5	18.1	17.9	18.4	18.8
	4H	17.6	18.1	18.0	18.4	18.8	17.6	18.1	18.0	18.4	18.8
	6H	17.9	18.3	18.3	18.7	19.2	17.7	18.1	18.1	18.5	18.9
	8H	18.1	18.5	18.5	18.9	19.3	17.7	18.1	18.1	18.5	18.9
	12H	18.2	18.5	18.7	19.0	19.4	17.7	18.0	18.1	18.4	18.9
8H	4H	17.7	18.1	18.1	18.5	18.9	18.1	18.5	18.5	18.9	19.3
	6H	18.1	18.4	18.6	18.9	19.4	18.3	18.6	18.7	19.0	19.5
	8H	18.4	18.6	18.8	19.1	19.6	18.4	18.6	18.8	19.1	19.6
	12H	18.6	18.8	19.1	19.3	19.8	18.4	18.7	18.9	19.1	19.7
12H	4H	17.7	18.0	18.1	18.4	18.9	18.2	18.5	18.7	19.0	19.4
	6H	18.2	18.4	18.6	18.9	19.4	18.4	18.7	18.9	19.2	19.7
	8H	18.4	18.7	18.9	19.1	19.7	18.6	18.8	19.1	19.3	19.8
Variations with the observer position at spacing:											
S =		1.0H					2.1 / -1.7				
		1.5H					4.2 / -2.1				
		2.0H					5.9 / -2.2				