

Last information update: March 2025

Product configuration: RN79(BR)

RN79: Pendant-mounted luminaire - Ø114 - General Light



Product code

RN79: Pendant-mounted luminaire - Ø114 - General Light

Technical description

Direct light luminaire - pendant-mounted installation. LED lamp with high color rendering index - high efficiency emission for general lighting uses. The light emission unit is made of PMMA and consists of a transparent prismatic reflector combined with a flux enhancer and diffuser screen - an internal polycarbonate cover defines the optical assembly visually. The twin-part external structure of the lighting body is made of machined aluminium - with a uniform or combined paint finish. The practical bayonet coupling system allows the two sections to be separated in order to perform all the preliminary pendant operations. The upper part of the lighting body is designed to adjust the length, wiring and locking of the pendant/power cables supplied with the accessory base that is indispensable for completing the product. DALI dimmable power supply driver integrated in the base. The PURE version of the luminaire stands out for its textured translucent external lower ring.

Installation

pendant-mounted installation with accessory base to be ordered separately.

Colour

White/White Transparent (G0) | Black/Black Transparent (G1) |
Black/White Transparent (G2) | White-Champagne/White
Transparent (I1) | White-Champagne/Black Transparent (I2) |
Black-Champagne/White Transparent (I3) | Black-
Champagne/Black Transparent (I4) | White/Black Transparent
(M6) | White/Transparent/White Transparent (R4) |
Black/Transparent/White Transparent (R5) |
Champagne/Transparent/White Transparent (R6) |
White/Transparent/White Transparent (R7) |
Black/Transparent/Black Transparent (R8) |
Champagne/Transparent/Black Transparent (R9)

Weight (Kg)

0.37

Mounting

ceiling pendant

Wiring

Driver integrated in accessory base - wiring terminal block and safety cable clamps positioned in the upper section of the structure.

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	1443.2	Colour temperature [K]:	4000
W system:	13.2	MacAdam Step:	2
Im source:	1760	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
W source:	11	Lamp code:	LED
Luminous efficiency (Im/W, 109.33 real value):		Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0.0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	82	LED current [mA]:	0.35
Beam angle [°]:	61°	Control:	DALI-2
CRI:	90		