


Last information update: March 2025

Product configuration: RP13(BR)

RP13: Pendant-mounted luminaire - UP/DOWN - Ø234 - UGR < 19

**Product code**


RP13: Pendant-mounted luminaire - UP/DOWN - Ø234 - UGR < 19

Technical description

Direct and indirect lighting luminaire - pendant installation. LED source with high colour rendering index - lower component with controlled luminance emission $L < 3000 \text{ cd/m}^2$ - UGR < 19 - ideal for environments with video screen use. PMMA emission unit made up of a transparent PMMA prismatic reflector in combination with the flow recovery unit and diffuser screen - an internal polycarbonate cover visually defines the optics unit. Indirect light with diffused emission - PMMA screen with superficial texture. External structure of the light unit with double element in machined aluminium - finished with an even or combined painting. The practical bayonet coupling system allows for the two sections to be separated to perform all the operations prior to hanging. The upper part of the light unit is set up to be adjusted lengthwise, wired and to block the suspension cables/accessory power supply unit provided that is essential for completing the product. Two dimmable DALI power supplies are included in the base (to be ordered separately) that allow the Luce UP and Luce DOWN to be used separately.

Installation

Pendant installation with accessory base unit to be ordered separately.

**Colour**

White/White Transparent (G0) | Black/Black Transparent (G1) |
Black/White Transparent (G2) | White-Champagne/White
Transparent (I1) | White-Champagne/Black Transparent (I2) |
Black-Champagne/White Transparent (I3) | Black-
Champagne/Black Transparent (I4) | White/Black Transparent
(M6) | White/Transparent/White Transparent (R4) |
Black/Transparent/White Transparent (R5) |
Champagne/Transparent/White Transparent (R6) |
White/Transparent/White Transparent (R7) |
Black/Transparent/Black Transparent (R8) |
Champagne/Transparent/Black Transparent (R9)

Weight (Kg)

1.84

Mounting

ceiling pendant

Wiring

Driver integrated into the accessory base unit - cabling terminal board and safety cable clamp positioned in the upper section of the structure.

Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	4728.8	Colour temperature [K]:	3000
W system:	41.6	MacAdam Step:	2
Im source:	5140	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
W source:	36	Lamp code:	LED
Luminous efficiency (Im/W, real value):	113.67	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	2520.92	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	92	LED current [mA]:	0.55
CRI:	90	Control:	DALI-2