

Last information update: April 2025

Product configuration: RP28.Q2

RP28.Q2: DownLight emission module - Frameless - L= 1140 - 48Vdc (PWM) - General Light - Space Optic – Neutral White - Sapphire blue/Black Transparent

Product code

RP28.Q2: DownLight emission module - Frameless - L= 1140 - 48Vdc (PWM) - General Light - Space Optic – Neutral White - Sapphire blue/Black Transparent

Technical description

Direct emission linear modular lighting system with Neutral White CRI90 monochrome LED lamps. General Light (High Output) luminaire with Opti-Diamond Space optic available in a White Cover (Transparent white) or Black Cover (Transparent black) version. Complete with 48Vdc Mid-Power Led circuit and PWM control system. Frameless version with extruded aluminium profile; Modular luminaire that can be positioned freely as it rotates 360° around its own axis (See the instruction sheet for the accessories to be used).

Installation

Pendant or surface-mounted using suitable accessories to be ordered separately.

Colour

Sapphire blue/Black Transparent (Q2)

Weight (Kg)

0.63


Wiring

Connection with quick coupling input and output connectors. The module is designed to use suitable Led Strips (Up Light emission) to be ordered separately. Power supply unit (48V) to be ordered separately as specified in the instruction sheet. Available in an ON-OFF, DALI and BLE version.

Complies with EN60598-1 and pertinent regulations




IP20

**Technical data**

Im system:	1968	MacAdam Step:	3
W system:	17.5	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Im source:	2660	Voltage [Vin]:	48
W source:	15	Lamp code:	LED
Luminous efficiency (lm/W, real value):	112.5	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	74	LED current [mA]:	72
CRI (minimum):	90	Control:	PWM
Colour temperature [K]:	4000		

Polar

Imax=2085 cd C5-185		Lux				
h	d1	d2	Em	Emax		
4	4.6	4.6	100	128		
8	9.1	9.2	25	32		
12	13.7	13.9	11	14		
16	18.2	18.5	6	8		



Isolux

