

## Libera Stand-alone


Design Artec  
Studio

iGuzzini

Last information update: April 2025

### Product configuration: RQ22.M6

RQ22.M6: Luminaire with Up/Down emission L=1828 - General Light - High Output - Space Frameless optic -- 39.2W 5065.5lm - 3500K - CRI 90 - White/Black Transparent



### Product code

RQ22.M6: Luminaire with Up/Down emission L=1828 - General Light - High Output - Space Frameless optic -- 39.2W 5065.5lm - 3500K - CRI 90 - White/Black Transparent

### Technical description

Direct (70%) / Indirect (30%) emission luminaire with 3500K CRI90 monochrome LED lamps. Opti-Diamond (High Output) Down General Light Space optic available in a White Cover (Transparent white) or Black Cover (Transparent black) version. Up General Light optic with opal screen. Frameless version extruded aluminium profile with die-cast zamak end caps. Complete with power and pendant cable L=3000. Steel pendant mount cable with millimetric adjustment system and brass component. Ceiling-mounted base in painted aluminium with galvanised steel wall plate. Product supplied with DALI dimmable electronic power supply unit positioned inside the aluminium base.

### Installation

Pendant-mounted. Complete with power and pendant cables L=3000 with brass ceiling-fixing component

### Colour

White/Black Transparent (M6)

### Weight (Kg)

1.81

### Mounting

ceiling pendant


### Wiring

Product complete with DALI power supply unit positioned inside the base.

Complies with EN60598-1 and pertinent regulations



IP20



### Technical data

lm system: 4605  
W system: 35  
lm source: 6140  
W source: 35  
Luminous efficiency (lm/W, real value): 131.6  
lm in emergency mode: -  
Total light flux at or above an angle of 90° [Lm]: 1693  
Light Output Ratio (L.O.R.) [%]: 75

CRI (minimum): 90  
Colour temperature [K]: 3500  
MacAdam Step: 3  
Lamp code: LED  
Number of lamps for optical assembly: 1  
ZVEI Code: LED  
Number of optical assemblies: 1  
Control: DALI-2

### Polar

