

Libera Stand-alone


Design Artec
Studio

iGuzzini

Last information update: April 2025

Product configuration: RQ23.M6

RQ23.M6: Luminaire with Up/Down emission L=1828 - General Light - High Output - Space Frameless optic - Neutral White -- 39.2W 5222.3lm - 4000K - CRI 90 - White/Black Transparent



Product code

RQ23.M6: Luminaire with Up/Down emission L=1828 - General Light - High Output - Space Frameless optic - Neutral White -- 39.2W 5222.3lm - 4000K - CRI 90 - White/Black Transparent

Technical description

Direct (70%) / Indirect (30%) emission luminaire with Neutral White CRI90 monochrome LED lamps. Opti-Diamond (High Output) Down General Light Space optic available in a White Cover (Transparent white) or Black Cover (Transparent black) version. Up General Light optic with opal screen. Frameless version extruded aluminium profile with die-cast zamak end caps. Complete with power and pendant cable L=3000. Steel pendant mount cable with millimetric adjustment system and brass component. Ceiling-mounted base in painted aluminium with galvanised steel wall plate. Product supplied with DALI dimmable electronic power supply unit positioned inside the aluminium base.

Installation

Pendant-mounted. Complete with power and pendant cables L=3000 with brass ceiling-fixing component

Colour

White/Black Transparent (M6)

Weight (Kg)

1.81

Mounting

ceiling pendant


Wiring

Product complete with DALI power supply unit positioned inside the base.

Complies with EN60598-1 and pertinent regulations



IP20



Technical data

lm system: 4748
W system: 35
lm source: 6330
W source: 35
Luminous efficiency (lm/W, real value): 135.6
lm in emergency mode: -
Total light flux at or above an angle of 90° [Lm]: 1746
Light Output Ratio (L.O.R.) [%]: 75

CRI (minimum): 90
Colour temperature [K]: 4000
MacAdam Step: 3
Lamp code: LED
Number of lamps for optical assembly: 1
ZVEI Code: LED
Number of optical assemblies: 1
Control: DALI-2

Polar

