

Libera Stand-alone

Design Artec
Studio

iGuzzini

Last information update: April 2025

Product configuration: RS46.M6

RS46.M6: Luminaire with Up/Down emission L=1428 - General Light - High Output - Space Frameless optic - Warm White -- - 32W
4017.8lm - 3000K - CRI 90 - White/Black Transparent

Product code

RS46.M6: Luminaire with Up/Down emission L=1428 - General Light - High Output - Space Frameless optic - Warm White -- - 32W
4017.8lm - 3000K - CRI 90 - White/Black Transparent

Technical description

Direct (70%) / Indirect (30%) emission luminaire with Warm White CRI90 monochrome LED lamps. Opti-Diamond (High Output) Down General Light Space optic available in a White Cover (Transparent white) or Black Cover (Transparent black) version. Up General Light optic with opal screen. Frameless version extruded aluminium profile with die-cast zamak end caps. Complete with power and pendant cable L=3000. Steel pendant mount cable with millimetric adjustment system and brass component. Ceiling-mounted base in painted aluminium with galvanised steel wall plate. Product supplied with DALI dimmable electronic power supply unit positioned inside the aluminium base.

Installation

Pendant-mounted. Complete with power and pendant cables L=3000 with brass ceiling-fixing component

Colour

White/Black Transparent (M6)

Weight (Kg)

1.55

Mounting

ceiling pendant

Wiring

Product complete with DALI power supply unit positioned inside the base.

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	3653	CRI (minimum):	90
W system:	29	Colour temperature [K]:	3000
Im source:	4870	MacAdam Step:	3
W source:	29	Lamp code:	LED
Luminous efficiency (Im/W, real value):	125.9	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	1343	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	75	Control:	DALI-2

Polar

